

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Giftmas

Supplier's address: SB E-commerce B.V., Edisonweg 3a, 3404LA IJsselstein Utrecht, NL

Model identifier: 000-177

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Mains		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters


Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	4	Energy efficiency class	G
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	60 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	3,5	Standby power (P_{sb}), expressed in W and rounded to the second decimal	-
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	60
Outer dimensions without separate control gear, lighting control	Height	1 000	Spectral power distribution in the range 250 nm to 800 nm, at full-load See image in last page
	Width	4	
	Depth	4	

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,478 0,429	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-65	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,92	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,1	

(a) '-': not applicable;

(b) '-': not applicable;

Photometric test record of one lamp at initial measurement:



EPREL registration number: 2757184 Model placed on the Union market from 11/06/2026.	 https://eprel.ec.europa.eu/qr/2757184
Supplier: SB E-commerce B.V. (Manufacturer)	Website:
Customer care service: Name: SB E-commerce B.V. Email: info@sbe-commerce.net Address: Edisonweg 3a 3404LA IJsselstein Netherlands Website: Phone: +31 6 45 81 10 86	