

VISITOR METAL FREE

Non magnetic safety cap overshoe



REF « VMF »

- Composition: Rubber and protective toe cap in fibreglass
- Professional use : Against impacts and toe crush injuries.
- ✓ Fibreglass toe cap : Metal free and ultra light !
- ✓ Rivets in nylon
- ✓ Velcro comfort strap: 3 sizes to cover from 34 to 50
- ✓ Color code to track sizes
- ✓ Can be adapted to all kind of footwear (even high-heeled shoes)
- ✓ Reusable
- ✓ Tiger-grip® antislip sole with self cleaning studs

Certifications

PPE REGULATION (EU) :
2016/425

(personal protective equipment)



EUROPEAN STANDARDS

CE certification :

- NF EN ISO 20345 / 2011
- NF 12568
- HAP / ORGANO



CE PPE CERTIFIED risk II

Certified organism:

CTC N° 0075/69367 Lyon - France



AMERICAN STANDARDS

- ASTM F 2413-11

• EN ISO 20345 – Toe cap resistance

200 joules resistance and resistant to crushing under max. Load of 1500 DaN

Physico-mechanical test

Test	Standard	VISITOR NON MAGNETIC results	Unit
Impact resistance (clearance after impact 200J)	EN ISO 20345	36	mm
Compressive resistance (clearance after compression 15kN)	EN ISO 20345	30	mm
Abrasion resistance (volume loss)	EN ISO 20345	140	mm ³
Slip resistance SRA (flat)	EN ISO 20345	0.36	flat friction
Slip resistance SRB (flat)	EN ISO 20345	0.26	flat friction

Sizes

	S				M						XL				
EU Sizes	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48 +
UK Sizes	1	2	3	4	5	6	6,5	7	8	9	10	10,5	11	12	13 +
US Woman	4	5	6	7	7,5	8	8,5	9,5	10	11					
US Man					5,5	6	7	8	8,5	9,5	10	11	11,5	12,5	13 +

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

The color code for Visitor Metal Free is on the front spoiler of the toe cap

Storage and maintenance



- Hand washable - Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°C.