



EN 55032:2015
EN 55035:2017
EN 61000-3-2:2014
EN 61000-3-3:2013

TEST REPORT

For

DONG GUAN ZHONG QIAN ELECTRONIC CO.,LTD

NO.8 MU LING STREET,GANG ZI VILLAGE, CHANG PING TOWN,
DONG GUAN CITY

Tested Model: ZQ104-1
Multiple Models: ZQ104-2, ZQ104-3

Report Type: Original Report	Product Type: Flying Finger Top
Report Number:	RSZ191016810-01
Report Date:	2019-10-25
	Joson Xiao
Reviewed By:	EMC Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk *. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE	5
RELATED SUBMITTAL(S)/GRANT(S).....	5
PERFORMANCE CRITERION	5
TEST METHODOLOGY	6
MEASUREMENT UNCERTAINTY	7
SYSTEM TEST CONFIGURATION.....	8
JUSTIFICATION	8
EUT EXERCISE SOFTWARE	8
EQUIPMENT MODIFICATIONS	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST REPORT.....	10
TEST EQUIPMENT LIST	11
EN 55032 §A.3 - CONDUCTED DISTURBANCE& CONDUCTED DISTURBANCE AT TELECOMMUNICATION PORT.....	13
APPLICABLE STANDARD	13
TEST SYSTEM SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	14
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	14
EN 55032 §A.2-RADIATED DISTURBANCE	17
APPLICABLE STANDARD	17
TEST SYSTEM SETUP.....	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	18
EN 55035 §4.2.1-ELECTROSTATIC DISCHARGES (IEC 61000-4-2).....	21
TEST SYSTEM SETUP.....	21
TEST STANDARD	21
TEST PROCEDURE	22
TEST DATA	22
EN 55035 §4.2.2.2-CONTINUOUS RADIATED IMMUNITY (IEC 61000-4-3)	26
TEST SYSTEM SETUP	26
TEST STANDARD	26
TEST PROCEDURE	27
TEST DATA	27
EN 55035 §4.2.2.3-CONTINUOUS CONDUCTED IMMUNITY (IEC 61000-4-6).....	29

TEST SETUP.....	29
TEST STANDARD	29
TEST PROCEDURE	29
TEST DATA	30
EN 55035 §4.2.3-POWER FREQUENCY MAGNETIC FIELDS (IEC 61000-4-8).....	31
TEST SETUP.....	31
TEST STANDARD	31
TEST PROCEDURE	31
TEST DATA AND SETUP PHOTO.....	32
EN 55035 §4.2.4-ELECTRICAL FAST TRANSIENTS (IEC 61000-4-4)	34
TEST SYSTEM SETUP.....	34
TEST STANDARD	34
TEST PROCEDURE	34
TEST DATA	35
EN 55035 §4.2.5-SURGES (IEC 61000-4-5)	36
TEST SYSTEM SETUP.....	36
TEST STANDARD	36
TEST PROCEDURE	36
TEST DATA	37
EN 55035 §4.2.6-VOLTAGE DIPS AND INTERRUPTIONS (IEC 61000-4-11).....	38
TEST SETUP.....	38
TEST STANDARD	38
TEST PROCEDURE	38
TEST DATA	38
EN 61000-3-2 – HARMONIC CURRENT EMISSIONS.....	40
EN 61000-3-3 – VOLTAGE FLUCTUATION AND FLICKER.....	41
TEST SYSTEM SETUP	41
TEST STANDARD	41
TEST DATA	42
EXHIBIT A - PRODUCT CE LABELING.....	44
PROPOSED CE LABEL FORMAT	44
PROPOSED LOCATION OF LABEL ON EUT	44
EXHIBIT B - EUT PHOTOGRAPHS	45
EUT – ALL VIEW	45
EUT – FRONT VIEW	45
EUT – REAR VIEW	46
EUT – TOP VIEW	46
EUT – BOTTOM VIEW	47
EUT – LEFT VIEW	47
EUT – RIGHT VIEW	48
EUT – COVER OFF VIEW 1	48
EUT – COVER OFF VIEW 2	49
EUT – COVER OFF VIEW 3	49
EUT – COVER OFF VIEW 4	50
EUT – MAIN BOARD TOP VIEW	50
EUT – MAIN BOARD BOTTOM VIEW	51
EUT – LED VIEW	51
EUT – MOTOR VIEW	52
EUT – BATTERY TOP VIEW	52
EUT – BATTERY BOTTOM VIEW	53
EUT – USB CABLE VIEW	53
EXHIBIT C - TEST SETUP PHOTOGRAPHS	54

TEST MODE: CHARGING	54
CONDUCTED DISTURBANCE AT MAINS TERMINALS - FRONT VIEW	54
CONDUCTED DISTURBANCE AT MAINS TERMINALS - SIDE VIEW.....	54
RADIATED EMISSIONS FRONT VIEW (BELOW 1GHZ).....	55
RADIATED EMISSIONS REAR VIEW (BELOW 1GHZ).....	55
TEST MODE: WORKING	56
RADIATED EMISSIONS VIEW (BELOW 1GHZ)	56
PRODUCT SIMILARITY DECLARATION LETTER	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Flying Finger Top
Tested Model	ZQ104-1
Multiple Model	ZQ104-2, ZQ104-3
Voltage Range	DC 3.7V from battery
Date of Test	2019-10-21 to 2019-10-23
Sample serial number	191016810(Assigned by Shenzhen BACL)
Received date	2019-10-16
Sample/EUT Status	Good condition

Notes: This series products model: ZQ104-2, ZQ104-3 and ZQ104-1 are identical schematics. Model ZQ104-1 was selected for fully testing, the detailed information can be referred to the declaration letter.

Objective

This test report is prepared on behalf of *DONG GUAN ZHONG QIAN ELECTRONIC CO.,LTD* in accordance with EN 55032: Electromagnetic compatibility of multimedia equipment -Emission Requirements. EN 55035: Electromagnetic compatibility of multimedia equipment -Immunity requirements. EN 61000-3-2, Limits – Limits for harmonic current emissions (equipment input current up to and including 16 A per phase), and also in accordance with EN 61000-3-3, Limits Section 3; Limitation of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current<16A.

The objective is to determine the compliance of EUT with EN 55032, EN 55035, EN 61000-3-2 and EN 61000-3-3.

Related Submittal(s)/Grant(s)

No related submittal(s).

Performance criterion

Performance criterion A

The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended.

The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion B

During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test. After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.

Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

Test Methodology

All measurements contained in this report were conducted with CISPR 16-1-1:2010+A1:2010+A2:2014, specification for radio disturbance and immunity measuring apparatus and methods P1-1: radio disturbance and immunity measuring apparatus measuring apparatus. CISPR16-1-4:2010+A1:2012 , Specification for radio disturbance and immunity measuring apparatus and methods-Part 1-4: Radio disturbance and immunity measuring apparatus -Ancillary equipment -Radiated disturbances. CISPR 16-2-1:2014, specification for radio disturbance and immunity measuring apparatus and methods P2-1: methods of measurement of disturbance and immunity conducted disturbance measurements. CISPR 16-2-3:2010+A1:2010+A2:2014, specification for radio disturbance and immunity measuring apparatus and methods P2-3 methods of measurement of disturbances and immunity radiated disturbance measurements. CISPR 16-4-2:2011, Specification for radio disturbance and immunity measuring apparatus and methods-Part 4-2: Uncertainties, statistics and limit modeling-Uncertainty in EMC measurements.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 Meters.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will be taken into consideration for the test data recorded in the report

Item		Expanded Measurement uncertainty
Conducted Emissions	AC Mains	1.95 dB (k=2, 95% level of confidence)
Radiated emission	Below 1GHz	4.75 dB (k=2, 95% level of confidence)
	Above 1GHz	4.88 dB (k=2, 95% level of confidence)

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in normal mode.

EUT exercise software

No software was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
BULL	Socket	GN-212	A37209315081183
ACT	Adapter	APS-FB018WE-G	19062700003

External I/O Cable


Cable Description	Length (m)	From/Port	To
Un-shielded Un-detachable AC cable	1.0	Socket	LISN
Un-shielded detachable DC cable	1.6	Adapter	EUT

Block Diagram of Test Setup

Test mode: Charging



Test mode: Working



SUMMARY OF TEST REPORT

EN 55032

RULE	DESCRIPTION	RESULTS
§ A.3	Conducted Disturbance at Mains Terminals	Compliance
§ A.2	Radiated Disturbance	Compliance

EN 55035

RULE	DESCRIPTION	RESULTS
§4.2.1	Electrostatic Discharge IEC 61000-4-2	Compliance
§4.2.2.2	Continuous Radiated Immunity IEC 61000-4-3	Compliance
§4.2.2.3	Continuous Conducted Immunity IEC 61000-4-6	Compliance
§4.2.3	Power Frequency Magnetic Fields IEC 61000-4-8	Compliance
§4.2.4	Electrical Fast Transients IEC 61000-4-4	Compliance
§4.2.5	Surges IEC 61000-4-5	Compliance
§4.2.6	Voltage Dips And Interruptions, IEC 61000-4-11	Compliance
§4.2.7	Broadband impulsive conducted disturbances	Not Applicable

EN 61000-3-2

Rule	Description	Results
§7	Harmonic Current Emissions	Compliance

EN 61000-3-3

Rule	Description	Results
§5	Voltage Fluctuation and Flicker	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMI					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2019-07-09	2020-07-08
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2019-01-25	2020-01-25
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2019-03-02	2020-03-01
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2019-07-09	2020-07-08
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	Auto test Software	EMC32	V9.10	NCR	NCR
EM Test	Harmonic/Flicker Analyzer	DPA 500N	V0939105176	2019-01-25	2020-01-25
EM Test	AC Source	ACS500	303276	2018-12-25	2019-12-25
EM Test	Test Software	DPA. Control	V5.0.3.0	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMS					
TESEQ	ESD Generator	NSG 438	1476	2019-08-13	2020-08-12
EM Test	EMS Combination Tester	UCS 500 N5	V0939105172	2019-03-02	2020-03-01
EM Test	AC Source	MV2616	V0939105173	2019-03-02	2020-03-01
HP	Signal Generator	8648C	3426A01345	2019-07-10	2020-07-09
A&R	Power Amplifier	500W100B	0348446	NCR	NCR
A&R	Power Amplifier	60S1G6	0348712	NCR	NCR
A&R	Antenna	ATL80M1G	348837	NCR	NCR
A&R	Antenna	ATT700M12G	0349411	NCR	NCR
Agilent	Signal Generator	8665B	3744A01692	2019-08-13	2020-08-12
A&R	RF Power Amplifier	15A250	13444	NCR	NCR
COM-POWER CORPORATION	CDN	CDN M325E	521145	2019-07-09	2020-07-08
WEINSCHEL	6dB Attenuator	50-6	R4376	NCR	NCR
EM TEST	Current Transformer	MC 2630	0309-59	NCR	NCR
EM TEST	Loop Antenna	MS100	0809-05	NCR	NCR
EW BELL	ELF Gauss/Tesla Meter	4190	911011	2019-01-28	2020-01-28
BACL	Test Software	VEE PRO	V2.3 VXE	NCR	NCR
EM Test	Test Software	IEC. Control	V5.0.9.0	NCR	NCR


*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

EN 55032 §A.3 - CONDUCTED DISTURBANCE & CONDUCTED DISTURBANCE AT TELECOMMUNICATION PORT

Applicable Standard

According to EN 55032 §A.3

Test System Setup



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is in accordance with CISPR 16-1-1:2010+A1:2010+A2:2014, CISPR 16-2-1:2014. The related limit was specified in the EN 55032 Class B.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN/ISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the limit of EN 55032 Class B

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Geng on 2019-10-21.

EUT Operation Mode: Charging

AC 230V/50 Hz, Line

Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave./QP)
0.348750	33.6	19.9	59.0	25.4	QP
0.356630	34.0	19.9	58.8	24.8	QP
0.573510	32.4	19.8	56.0	23.6	QP
0.884590	33.7	19.8	56.0	22.3	QP
0.987390	33.8	19.9	56.0	22.2	QP
1.054070	33.3	19.9	56.0	22.7	QP
0.348750	28.5	19.9	49.0	20.5	Ave.
0.356630	27.7	19.9	48.8	21.1	Ave.
0.573510	22.3	19.8	46.0	23.7	Ave.
0.884590	26.6	19.8	46.0	19.4	Ave.
0.987390	27.6	19.9	46.0	18.4	Ave.
1.054070	27.3	19.9	46.0	18.7	Ave.

AC 230V/50 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/Ave./QP)
0.566370	35.2	19.8	56.0	20.8	QP
0.813910	30.8	19.8	56.0	25.2	QP
0.895230	32.5	19.7	56.0	23.5	QP
0.975150	32.3	19.8	56.0	23.7	QP
1.038310	32.9	19.8	56.0	23.1	QP
1.124930	29.8	19.8	56.0	26.2	QP
0.574000	26.6	19.8	46.0	19.4	Ave.
0.806000	25.1	19.8	46.0	20.9	Ave.
0.846000	24.5	19.8	46.0	21.5	Ave.
0.998000	28.6	19.8	46.0	17.4	Ave.
1.014000	27.2	19.8	46.0	18.8	Ave.
1.126000	24.7	19.8	46.0	21.3	Ave.

Note:

- 1) Correction Factor =LISN/ISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


EN 55032 §A.2-RADIATED DISTURBANCE

Applicable Standard

EN 55032 §A.2

Test System Setup

Below 1 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the CISPR16-1-4:2010+A1:2012, CISPR 16-2-3:2010+A1:2010+A2:2014. The limit was specified in EN 55032 Class B.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in the Quasi-peak detection mode for below 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}.$$

Test Results Summary

According to the data in the following table, the EUT complied with the limit of EN 55032 Class B

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\lim} + U_{\text{cisp}}$$

In BACL., $U_{(Lm)}$ is less than $+ U_{\text{cisp}}$, if L_m is less than L_{\lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Steve Lan on 2019-10-21.

EUT Operation Mode: Charging


30 MHz~1 GHz



Frequency (MHz)	Corrected Amplitude (dB μ V/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
78.906375	21.88	102.0	V	158.0	-20.0	40.00	18.12
85.685250	18.93	171.0	V	141.0	-19.4	40.00	21.07
168.273000	19.21	167.0	H	81.0	-14.8	40.00	20.79
186.900625	28.11	215.0	H	77.0	-15.2	40.00	11.89
371.668750	22.36	137.0	H	64.0	-10.6	47.00	24.64
837.497875	28.66	103.0	V	31.0	5.7	47.00	18.34

EUT Operation Mode: Working

30 MHz~1 GHz




Frequency (MHz)	Corrected Amplitude (dB μ V/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
30.363750	19.94	100.0	H	0.0	-7.9	40.00	20.06
35.213750	18.62	100.0	V	261.0	-10.6	40.00	21.38
460.316250	22.99	100.0	V	225.0	-8.0	47.00	24.01
595.873750	27.28	300.0	H	36.0	-1.9	47.00	19.72
836.070000	35.24	300.0	H	183.0	5.5	47.00	11.76
897.301250	33.15	300.0	V	117.0	4.3	47.00	13.85

Note:

- 1) Corrected Amplitude = Meter Reading + Correction Factor
- 2) Correction Factor = Antenna Factor + Cable Loss - Amplifier Gain
- 3) Margin = Limit – Corrected Amplitude

EN 55035 §4.2.1-ELECTROSTATIC DISCHARGES (IEC 61000-4-2)

Test System Setup



IEC 61000-4-2 specifies that a tabletop EUT shall be placed on a non-conducting table which is 80 centimeters above a ground reference plane and that floor mounted equipment shall be placed on a insulating support approximately 10 centimeters above a ground plane. During the tests, the EUT is positioned over a ground reference plane in conformance with this requirement.

For tabletop equipment, a 1.6 by 0.8-meter metal sheet (HCP) is placed on the table and connected to the ground plane via a metal strap with two 470 k Ohms resistors in series. The EUT and attached cables are isolated from this metal sheet by 0.5-millimeter thick insulating material. A Vertical Coupling Plane (VCP) grounded on the ground plane through the same configuration as in the HCP is used.

Test Standard

EN 55035:2017 (IEC 61000-4-2:2008)
 Air Discharge at ± 2 kV; ± 4 kV; ± 8 kV
 Contact Discharge at ± 2 kV; ± 4 kV

Test Level

Level	Test Voltage Contact Discharge (\pm kV)	Test Voltage Air Discharge (\pm kV)
1.	2	2
2.	4	4
3.	6	8
4.	8	15
X.	Special	Special

Performance criterion: B

Test Procedure

Air Discharge:

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

Contact Discharge:

All the procedure shall be same as Section 8.3.1 of IEC 61000-4-2, except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

Indirect discharge for horizontal coupling plane

At least 20 single discharges shall be applied to the horizontal coupling plane, at points on each side of the EUT. The discharge electrode positions vertically at a distance of 0.1 m from the EUT and with the discharge electrode touching the coupling plane.

Indirect discharge for vertical coupling plane

At least 20 single discharges shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m × 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.

EUT Operation Mode: Charging

Table 1: Electrostatic Discharge Immunity (Air Discharge)

IEC 61000-4-2 Test Points	Test Levels							
	-2 kV	+2 kV	-4 kV	+4 kV	-8 kV	+8 kV	-15 kV	+15 kV
Front (1 point)	A	A	A	A	A	A	/	/
Top (2 points)	A	A	A	A	A	A	/	/
Bottom (1 point)	A	A	A	A	A	A	/	/

Table 2: Electrostatic Discharge Immunity (Direct Contact)

IEC 61000-4-2 Test Points	Test Levels							
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV
/	/	/	/	/	/	/	/	/

Table 3: Electrostatic Discharge Immunity (Indirect Contact HCP)



IEC 61000-4-2 Test Points	Test Levels							
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV
Front Side	A	A	A	A	/	/	/	/
Back Side	A	A	A	A	/	/	/	/
Left Side	A	A	A	A	/	/	/	/
Right Side	A	A	A	A	/	/	/	/

Table 4: Electrostatic Discharge Immunity (Indirect Contact VCP)


IEC 61000-4-2 Test Points	Test Levels							
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV
Front Side	A	A	A	A	/	/	/	/
Back Side	A	A	A	A	/	/	/	/
Left Side	A	A	A	A	/	/	/	/
Right Side	A	A	A	A	/	/	/	/



Note: represents air discharge, represents direct contact



Test Setup Photo

EN 55035 §4.2.2.2-CONTINUOUS RADIATED IMMUNITY (IEC 61000-4-3)**Test System Setup****Test Standard**

EN 55035:2017 (IEC 61000-4-3: 2006 + A1:2007 + A2:2010)
Test level 2 at 3V / m

Test Level

Level	Field Strength V/m
1.	1
2.	3
3.	10
X.	Special

Performance Criterion: A

Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above the ground. The EUT is set 3 meters away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarizations of the antenna are set on test. Each of the four sides of EUT must be faced this transmitting antenna and measured individually.

In order to judge the EUT performance, a CCD camera and PC are used to monitor the EUT.

All the scanning conditions are as follows:

Condition of Test	Remarks
1. Field Strength	3 V/m (Test level 2)
2. Radiated Signal	AM 80%, 1 kHz Modulation
3. Scanning Frequency	80 – 1000 MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz
4. Sweeping time of radiated	0.0015 decade/s
5. Dwell Time	1 sec.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.

EUT Operation Mode: Charging&Working

Frequency (MHz)	Front Side (3 V/m)		Rear Side (3 V/m)		Left Side (3 V/m)		Right Side (3 V/m)	
	VERT	HORI	VERT	HORI	VERT	HORI	VERT	HORI
80-1000	A	A	A	A	A	A	A	A
1800	A	A	A	A	A	A	A	A
2600	A	A	A	A	A	A	A	A
3500	A	A	A	A	A	A	A	A
5000	A	A	A	A	A	A	A	A

Charging




Working



Test Setup Photos

EN 55035 §4.2.2.3-CONTINUOUS CONDUCTED IMMUNITY (IEC 61000-4-6)

Test Setup



Test Standard

EN 55035:2017 (IEC 61000-4-6:2008)

Test Level

Frequency(MHz)	Voltage Level (r.m.s.) (V)
0.15 to 10	3
10 to 30	3 to 1
30 to 80	1

Performance Criterion: A

Test Procedure

- 1) Let the EUT work in test mode and test it.
- 2) The EUT are placed on an insulating support 0.1 m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3 m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).
- 3) The disturbance signal described below is injected to EUT through CDN.
- 4) The EUT operates within its operational mode(s) under intended climatic conditions after power on.
- 5) The frequency range is swept from 150 kHz to 80 MHz using 3V signal level, and with the disturbance signal 80% amplitude modulated with a 1 kHz sine wave.
- 6) The rate of sweep shall not exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.
- 7) An artificial ear and sound level meter are used to monitor the sound pressure level. RF communication test set is used to monitor the noise level.
- 8) Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.


EUT Operation Mode: Charging

AC Mains


Modulation: Amplitude 80%, 1 kHz sine wave

Test Level:

Frequency (MHz)	Voltage Level (r.m.s.) (V)	Pass	Fail
0.15 to 10	3	A	/
10 to 30	3 to 1	A	/
30 to 80	1	A	/
X	Special	/	/



Test Setup Photo

EN 55035 §4.2.3-POWER FREQUENCY MAGNETIC FIELDS (IEC 61000-4-8)**Test Setup****Test Standard**

EN 55035:2017 (IEC 61000-4-8:2009)
Test level 1 at 1A/m

Test Level

Level	Magnetic Field Strength A/m
1	1
2	3
3	10
4	30
5	100
X.	Special

Performance criterion: A**Test Procedure**

The EUT shall be subjected to the test magnetic field by using the induction coil of standard dimensions (1 m*1 m). The induction coil shall then be rotated by 90° in order to expose the EUT to the test field with different orientations.

Test Data and Setup Photo**Environmental Conditions**


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.


EUT Operation Mode: Charging&Working

Level	Magnetic Field Strength A/m	X (Horizontal)	Y (Vertical)	Z (Special)
1	1	A	A	A
2	3	/	/	/
3	10	/	/	/
4	30	/	/	/
5	100	/	/	/
X	Special	/	/	/

Charging




Working



Test Setup Photos

EN 55035 §4.2.4-ELECTRICAL FAST TRANSIENTS (IEC 61000-4-4)

Test System Setup



Test Standard

EN 55035:2017 (IEC 61000-4-4:2012)
Test level 2 at ± 1 kV for AC mains

Test Level

Open Circuit Output Test Voltage $\pm 10\%$		
Level	On Power Supply Lines	On I/O (Input/Output) Signal data and control lines
1	0.5 kV	0.25 kV
2	1 kV	0.5 kV
3	2 kV	1 kV
4	4 kV	2 kV
X	Special	Special

Performance Criterion: B

Test Procedure

The EUT was arranged for Power Line Coupling and for I/O Line Coupling through a capacitive clamp, where applicable. (Note: The I/O coupling test using a capacitive clamp is performed on the I/O interface cables that are longer in length than 3 meters.) A metal ground plane 2.4 meter by 2.0 meter was placed between the floor and the table and is connected to the earth by a 2.0 meter ground rod. The ground rod is connected to the test facility's electrical earth.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.

EUT Operation Mode: Charging


IEC 61000-4-4 Test Points		Test Levels (kV)							
		+0.5	-0.5	+1.0	-1.0	+2.0	-2.0	+4.0	-4.0
AC mains power input ports	L1	/	/	A	A	/	/	/	/
	N	/	/	A	A	/	/	/	/
	PE	/	/	/	/	/	/	/	/
	L1/N	/	/	A	A	/	/	/	/
	L1/PE	/	/	/	/	/	/	/	/
	N/PE	/	/	/	/	/	/	/	/
	L1/N/PE	/	/	/	/	/	/	/	/
Signal Port	/	/	/	/	/	/	/	/	/



Test Setup Photo

EN 55035 §4.2.5-SURGES (IEC 61000-4-5)

Test System Setup



Test Standard

EN 55035:2017 (IEC 61000-4-5:2005)
AC mains: Line to Line at $\pm 0.5\text{kV}$, $\pm 1\text{kV}$;

Test Level

Level	Open Circuit Output Test Voltage $\pm 10\%$	Performance Criterion	
		AC Mains	Signal Port
1	0.5 kV	B	C
2	1 kV	B	C
3	2 kV	B	C
4	4 kV	B	C
X	Special	/	/

Test Procedure

- 1) For input a.c. power ports, provide a $1.2/50\mu\text{s}$ voltage surge (at open-circuit condition) and a $8/20\ \mu\text{s}$ current surge into a short circuit.
- 2) For telecommunication port, provide a $10/700\mu\text{s}$ voltage surge (at open-circuit condition) and a $5/320\ \mu\text{s}$ current surge into a short circuit.
- 3) At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.
- 4) Different phase angles are done individually.
- 5) Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.

EUT Operation Mode: Charging

AC Mains Port


Level	Voltage	Poll	Path	Pass	Fail
1	0.5kV	±	L1/N	A	/
2	1kV	±	L1/N	A	/
3	2kV	±	L1/N, L1/PE, N/PE, L1/N/PE	/	/
4	4kV	±	L1/N, L1/PE, N/PE, L1/N/PE	/	/



Test Setup Photo

EN 55035 §4.2.6-VOLTAGE DIPS AND INTERRUPTIONS (IEC 61000-4-11)

Test Setup



Test Standard

EN 55035:2017 (IEC 61000-4-11:2004)
Test levels and Performance Criterion

Test Level	Voltage dip and short interruptions %UT	Duration (Periods)	Performance Criterion
1	>95	0.5	B
2	30	25	C
3	>95	250	C

Test Procedure

- 1) The interruption is introduced at selected phase angles with specified duration.
- 2) Record any degradation of performance.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Larry Li on 2019-10-23.

EUT Operation Mode: Charging

Level	U2 (% Reduction)	Td(Periods)	Phase Angle	N	Pass	Fail
1	100	0.5	0/180	3	A	/
2	30	25	0/180	3	A	/
3	100	250	0/180	3	B	/

Note: "B" means self-restoring after charging was broken off for a while during the testing.




Test Setup Photo

EN 61000-3-2 – HARMONIC CURRENT EMISSIONS

According to EN 61000-3-2:2014 section 7: Equipment with a rated power of 75 W or less, other than lighting equipment, are not included in this standard.

EN 61000-3-3 – VOLTAGE FLUCTUATION AND FLICKER

Test System Setup



Test Standard

According to EN 61000-3-3:2013

Flicker Test Limits:

The limits shall be applicable to voltage fluctuations and flicker at the supply terminals of the equipment under test, measured or calculated according to clause 4 under test conditions described in clause 6 and annex A. Tests made to prove compliance with the limits are considered to be type tests.

The following limits apply:

- the value of P_{st} shall not be greater than 1,0;
- the value of P_{lt} shall not be greater than 0,65;
- the value of $d(t)$ during a voltage change shall not exceed 3,3 % for more than 500 ms;
- the relative steady-state voltage change, d_c , shall not exceed 3,3 %;
- the maximum relative voltage change d_{max} , shall not exceed
 - a) 4 % without additional conditions;
 - b) 6 % for equipment which is:
 - switched manually, or
 - switched automatically more frequently than twice per day, and also has either a delayed restart (the delay being not less than a few tens of seconds), or manual restart, after a power supply interruption.
 - Note: The cycling frequency will be further limited by the P_{st} and P_{lt} limit. For example: a d_{max} of 6 % producing a rectangular voltage change characteristic twice per hour will give a P_{lt} of about 0.65.
 - c) 7 % for equipment which is
 - attended whilst in use (for example: hair dryers, vacuum cleaners, kitchen equipment such as mixers, garden equipment such as lawn mowers, portable tools such as electric drills), or
 - switched on automatically, or is intended to be switched on manually, no more than twice per day, and also has either a delayed restart (the delay being not less than a few tens of seconds) or manual restart, after a power supply interruption.

In the case of equipment having several separately controlled circuits in accordance with 6.6, limits b) and

c) shall apply only if there is delayed or manual restart after a power supply interruption; for all equipment with automatic switching which is energized immediately on restoration of supply after a power supply interruption, limits a) shall apply; for all equipment with manual switching, limits b) or c) shall apply

depending on the rate of switching. Pst and Plt requirements shall not be applied to voltage changes caused by manual switching. The limits shall not be applied to voltage changes associated with emergency switching or emergency interruptions.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

Date of test:	9:52 21.Oct 2019
Tester:	Larry Li
Standard used:	EN/IEC 61000-3-3 Flicker
Long time (Pst):	10 min
Observation time:	120 min (12 Flicker measurement)
Flicker meter:	230V / 50Hz
Customer:	DONG GUAN ZHONG QIAN ELECTRONIC CO.,LTD
E. U. T.:	Flying Finger Top
Model:	ZQ104-1
EUT operation mode:	Charging

Maximum Flicker results

	EUT values	Limit	Result
Pst	0.170	1.00	Pass
Plt	0.075	0.65	Pass
dc [%]	0.038	3.30	Pass
dmax [%]	0.861	4.00	Pass
dt [s]	0.000	0.50	Pass



Test Setup Photo

EXHIBIT A - PRODUCT CE LABELING

Proposed CE Label Format



Specification: The CE marking shall be affixed visibly, legibly and indelibly to the apparatus or to its data plate. Where that is not possible or not warranted on account of the nature of the apparatus, it shall be affixed to the packaging and to the accompanying documents.

Proposed Location of Label on EUT




EXHIBIT B - EUT PHOTOGRAPHS


EUT – All View



EUT – Front View



EUT – Rear View




EUT – Top View




EUT – Bottom View



EUT – Left View



EUT – Right View




EUT – Cover off View 1




EUT – Cover off View 2




EUT – Cover off View 3




EUT – Cover off View 4



EUT –Main Board Top View




EUT –Main Board Bottom View




EUT –LED View




EUT –Motor View



EUT – Battery Top View



EUT – Battery Bottom View




EUT – USB Cable View




EXHIBIT C - TEST SETUP PHOTOGRAPHS

**Test mode: Charging
Conducted Disturbance at Mains Terminals - Front View**



Conducted Disturbance at Mains Terminals - Side View



Radiated Emissions Front View (Below 1GHz)



Radiated Emissions Rear View (Below 1GHz)



**Test mode: Working
Radiated Emissions View (Below 1GHz)**



PRODUCT SIMILARITY DECLARATION LETTER

DONG GUAN ZHONG QIAN ELECTRONIC
CO.,LTD
NO.8 MU LING STREET,GANG ZI VILLAGE,
CHANG PING TOWN,DONG GUAN CITY
T: 13712270181

October 30, 2019

Product Similarity Declaration

To Whom It May Concern,

We, DONG GUAN ZHONG QIAN ELECTRONIC CO.,LTD , hereby declare that we have a product named as Flying Finger Top (Model number: ZQ104-1) was tested by BACL. Meanwhile, for our marketing purpose, we would like to list a series models of main board (ZQ104-2/ZQ104-3) on reports and certificate. All of the main boards are identical schematics, every series model have same EMC test data, the only difference is the color.

We confirm that all information above is true, and we'll be responsible for all the consequences. Please contact me if you have any question.

Signature: *Weibiao Wang*

Printed Name: Weibiao Wang

Title: Manager

***** END OF REPORT *****