
USER'S MANUAL





PDX-2608 PDX-2608 DUO


1 OVERVIEWS



handset onto the cradle/charger

(M 1) (N	Description 2 direct memory buttons BOOST button: during a call, press to en- able the extra amplifier				
R	R button: function button for certain telecom services ▲ and ▼ buttons: during a call, press to				
⇒/OK	in standby mode, press to open the menu				
	during setup, press to confirm your settings				
	correction button when entering phone numbers or names during setup, press to go back one step in stand-by mode, press to start an intercom call (PDX-2608 DUO only)				
) c/⊗	during a call, press to switch off the microphone				
	press to answer an incoming call or to start a phone conversation during a call, press again to enable or disable the speaker function				
	press to end a call press and hold (> 5 sec.) to switch off the handset				
	in standby mode, press to open the Caller-ID memory				
	in standby mode, press to open the last dialled number memory				
	press to scroll through memories or settings				
	0-9 buttons: to dial phone numbers and to enter memories				
	'asterisk' and 'pound' buttons: used for e.g. telecom banking				
Ĩ¥ [*≉	+ extra: button *: press and hold 2 seconds to lock and unlock the keyboard button #: press and hold 2 seconds so switch-OFF and ON the ringer signal				
	2				

1.2 DISPLAY:





 flashes when the connection between the handset and base is lost remains lit when the handset is within range of the base

flashes when receiving an external call
 remains lit during a call



flashes when receiving an internal call remains lit during an intercom call



illuminates when the speaker function is enabled



illuminates when checking the Caller-ID memory and having new calls

shows the status of the rechargeable batteries:

- **IIII** = batteries are full
- Image: Second state and second sec
- I = batteries are 1/3 full, recharge as soon as possible

Image: state is a state in the state in the state is a state in the state in the state is a state in the state in the state is a state in the state in th

the battery symbol will scroll while charging until the batteries are fully charged



illuminates when the number is too long to be shown in the display (press the # button to see the rest of the number)



illuminates when you've receiver a voicemail message (only FSK systems)




illuminates when the alarm (wake-up) function is enabled



illuminates when the ring volume is set to 0 (switched off)

1.3 BASE:



2 INSTALLATION

2.1 BASE STATION:


Telephone connection:

Plug the small connector at the phone cable into the back of the base station **7** (press the connector until you hear a click). Plug the phone connector into the phone socket.

Power supply:

Connect the supplied power adaptor to the — input at the rear of the base and insert the adaptor into a 230V wall socket.

ONLY CONNECT THE INCLUDED ADAPTER. CONNECTING OTHER ADAPTERS MAY RESULT IN DANGEROUS SITUA-TIONS OR MAY CAUSE DAMAGE TO THE ELECTRONICS OF THE PHONE.



2.2 HANDSET:

- 1. Open the battery compartment of the handset, by sliding the battery cover down.
- 2. Insert the batteries into the battery compartment; at this, pay attention to the polarity (+ and -).
- 3. Slide the battery cover back onto the handset and place the handset on the base station.
- 4. Leave the handset continuously during 15 hours on the base station, to charge the batteries properly.

INSERT ONLY RECHARGEABLE NIMH (NICKEL METAL HYDRIDE) BATTERIES. THE USE OF NON RECHARGE-ABLE BATTERIES MAY CAUSE DANGEROUS SITUATIONS OR EXPLOSION HAZARD.

2.3 EXTRA HANDSET AND CHARGER: (PDX-2608 DUO)

2 batteries and a charger with adapter will be included for every handset. Plug the adapter of these chargers in a 230 Volt mains socket, insert the batteries into the handset(s) and place the handset(s) on the charger(s) for 15 hours to charge the batteries.

3 CALLING

3.1 RECEIVING CALLS:

when you receive a call, the display lighting of the handset will switch on and the indicator at the top of the handset starts flashing



press the Call button to answer this call

• see paragraph 10.2, item [Auto antw] answering calls by only from the base station

3.2 CALLING WITH THE PHONE OR USING THE HANDS-FREE FUNCTION: You can make calls holding the handset against your ear or you can use the speaker function allowing other household members to listen in or to keep your hands free for e.g. making notes



during a call, press the Call button again to switch on the speaker function



press the Call button again to switch the speaker function back off

3.3 ENDING CALLS:



press the End button to disconnect your call

• you can also place the handset back onto the base or cradle/charger to disconnect a call

3.4 DIALLING NUMBERS:



Direct dialing:

Press the phone-on key and wait for the dial tone.



.123

4 5 6 7 8 9 Enter the phone number through the keyboard; this number will be dialed directly.

<u>pre-dialling:</u>

Enter the phone number through the keyboard.

- press and hold the 0 button for at least once second to insert a dialling pause (the display will show -P-)
- press the C button to delete any incorrect input



press the Call button to dial the number



dialling from the phonebook memory: press 2x the OK button



use the \blacktriangle and \blacktriangledown buttons to search for the desired memory



press the Call button to dial the number • see paragraph 7.3 for programming phonebook memories





dialling from the Caller-ID memory: press the \clubsuit ? button and use the \blacktriangle and \checkmark buttons to select the desired call



press the Call button to dial the selected number



dialling from the last dialled number memory: press the \bigcirc button and use the \blacktriangle and \checkmark buttons to select the desired call



press the Call button to dial the selected number



dialling speed-dial contacts press and hold the M1 or M2 button for 2 seconds

the handset will switch on and the number is dialled

• see paragraph 10.2, item [Snelkeuz] for programming these speed-dial memories

2 sec. .1 2 3 .4 5 6 .7 8 9

 \bigcirc


dialling direct memories

press and hold one of the 0-9 buttons on the keypad for at least 2 seconds

the handset will switch on and the number is dialled

3.5 TO MUTE THE MICROPHONE:

During a call, you can switch off the microphone allowing you to consult with other household members without having your call partner listening.



during a call, press the \otimes button to switch off the microphone;


press the & again to switch the microphone back on

3.6 RECEPTION VOLUME:



normal amplification:

during a call, use the ▲ and ▼ buttons to adjust the reception volume; for this you may also use the ▲ and ▼ buttons at the right side of the handset or the ▲ and ▼ buttons underneath the M2 button



boost apmplification:

first press the <a>the button at the left side of the handset; the indicator above the display will switch on

now use the \blacktriangle and \checkmark buttons to set the desired volume level

- the volume level for calling via the handset or hands-free can be set separately
- · the selected setting will be kept in the memory
- after disconnecting a call, the boost amplifier will be switched off automatically
- the boost amplifier level is +8dB

3.7 CALL DURATION:



during a call, the call duration will be shown in the display; the call duration will disappear from the display as soon as you disconnect

3.8 R/FLASH FUNCTION:


R/FLASH means you briefly interrupt the telephone connection. This function allows you to forward calls with certain home or office switchboards or activate telephone services such as 'Call waiting'.



during a call, press and hold the $\#/\mathbf{R}$ button for at least 2 seconds to emit a FLASH pulse

- Some telephone service providers require you to press a numeric button after giving the FLASH pulse to use e.g. 'Call Waiting'; contact your provider for more information.
- The interruption duration of the FLASH pulse can be adjusted; for this, see paragraph 11.2 [Flash].

3.9 HANDSET SEARCH FUNCTION:



3.10 TO SWITCH OFF THE HANDSET:

You can fully switch off the handset to save battery power or when you don't want to be disturbed:



press and hold the End button for 5 seconds; the handset will now switch itself off completely

press and hold again for 5 seconds to switch the handset back on (or place the handset onto the base/charger)

· keep in mind that you cannot call or be called while the handset is switched off

RE-DIALLING 4

41 INTRODUCTION:

The handset memorizes the 5 last dialled numbers. You can redial these numbers, save them in the phonebook memories or delete them.

4.2 TO REDIAL:



press the \bigcirc button and use the \blacktriangle and \checkmark buttons to select the desired last dialled number

press the Call button to dial the selected number

TO SAVE OR DELETE: 4.3



press the button and use the \blacktriangle and \blacktriangledown buttons to select the desired number

press the ok button



use the \blacktriangle and \checkmark buttons to choose one of the following options:



save:

select this option to add the number to the phonebook memory of the telephone (*)



<u>delete:</u>

use this option to only delete the selected call from the memory



<u>delete all:</u>

use this option to delete the entire last dialled number memory

*: when saving a number, you may set a ringtone that'll sound when that subscriber calls you; for this function you must be subscribed to the Caller-ID service

5 CALLER IDENTIFICATION

5.1 INTRODUCTION:

If you have the service Caller Identification at your disposal, the number of the calling party is displayed on the display of your handset(s). You have programmed this number including name and the phone book memory of the handset, the name is also displayed on the display and you can set an individual ringtone for each memory. Each handset has a memory for 10 calls.

5.2 INDICATION NEW CALLS:



The display of the handset shows how many new calls you've received since the last time you checked the memory.


5.3 VIEW MEMORY AND CALLBACK:



press the \blacktriangle ? button and use the \blacktriangle and \checkmark buttons to scroll the memory



if a name is shown, you can press the # button to display the number




new calls are indicated by a star in the display

the triangular arrow pointing to the right indicates that there are additional digits at the right side of the displayed number; press the # button to show these digits



press the Call button to dial the selected number

5.4 DETAILS, SAVE OR DELETE:



press the \clubsuit button and use the \blacktriangle and \blacktriangledown buttons to select the desired number

press the OK button

use the \blacktriangle and \blacktriangledown buttons to choose one of the following options:



<u>details:</u>

choose this option to show the date of the call, now press the # button to display the time of this call (*)



save:

select this option to add the number to the phonebook memory of the telephone



<u>delete:</u>

use this option to only delete the selected call from the memory



<u>delete all:</u> use this option to delete the entire last dialled number memory

5.5 ADDITIONAL INFORMATION:

- The PDX-2608 / PDX-2608 DUO is suitable for both the DTMF system, offered by the Dutch PTT and for the FSK system, offered by the Belgian PTT and by cable companies in the Netherlands and Belgium for as far as this service is offered.
- The Caller-ID service often requires an additional subscription; please contact your telephone service provider for more information.
- Name display:
 - the DTMF system doesn't send any names; the name will only appear in the display when you've programmed it in the phonebook memory of the handset
 - the FSK system does send names (ask your telephone service provider for more information)
- If the display shows [WITHHELD] or [000000000], the calling subscriber has blocked sending his or her name and number.
- The names/numbers of the calls you've answered are also saved.
- When using multiple handsets: memories must be deleted separately in each handset.

6 VOICEMAIL INDICATION

6.1 INTRODUCTION:

Voicemail is a service offered by the telephone service provider, allowing callers to leave a message. You can listen to this message at a later time. (*)

6.2 NEW VOICEMAIL INDICATION:



If your service provider supports voicemail, based on the FSK system, you may receive a notification when a new message has been left for you. This is indicated by the voicemail symbol (**OO**) in the display of your handset

this voicemail notification will disappear after you've listened to your message

- You can remove this notification also by resetting the settings, please see paragraph 12.2.
- For any questions about the voicemail function, please contact your telephone service provider.

7 PHONE BOOK MEMORY

7.1 INTRODUCTION:

Every PDX-2608 / PDX-2608 DUO handset has a phone book memory with a capacity of 20 phone numbers of at most 20 digits. You can program a name of at most 12 characters with each number. The phone book memory in the handset is connected to the function Caller Identification. When you are called by somebody, whose name and number you have programmed in the memory, the name of this person is also displayed beside the number on the display of your handset. (However, for this you need to subscribe to the service Caller Identification.)

7.2 SEARCHING FOR AND CALLING CONTACTS:



press 2x the ⇒ button to open the phonebook memory, the display will then show the name of the first contact or [EMPTY] appears when no contacts are saved

use the \blacktriangle and \checkmark buttons to scroll the memory you can also search using the keypad, for example press 2x the 5 button to search for the first contact starting with the letter K, now continue searching with the \blacktriangle and \checkmark buttons

press the Call button to dial the selected number

7.3 TO ADD, EDIT OR DELETE CONTACTS:

to add: press 4x the ⇒ button



↔/ok

4x

use the keypad to enter the name - use the C button to correct any incorrect input

- see the next page for all available characters



press the OK button



use the keypad to enter the phone number - use the C button to correct any incorrect input - briefly press and hold the 0 button to insert a dialling



press the OK button

pause



use the ▲ and ▼ buttons to select the desired melody that must sound when this subscriber calls you, to use this function *you must be subscribed to the Caller-ID service*



press the OK button to save this contact



press the End button to stop programming and return the handset to standby mode



to edit: press 2x the ⇒ button



use the \blacktriangle and \blacktriangledown buttons to select the contact you want to edit



press the OK button



use the \blacktriangle and \checkmark buttons to select the option [EDIT]



press the OK button



use the C button to delete the old name and use the keypad to enter the new name



press the OK button



use the C button to delete the old number and use the keypad to enter the new name



press the ok button



use the ▲ and ▼ buttons to select a different ringtone that must sound when this subscriber calls you



press the OK button to save this memory



press the End button to stop editing and return the handset to standby mode



to delete: press 2x the ⇒ button



use the \blacktriangle and \blacktriangledown buttons to select the contact you want to delete



press the OK button



use the ▲ and ▼ buttons to select the option [DELETE] to only delete the selected contact or select [DELETE ALL] to delete all contacts



press the OK button when using [DELETE ALL] you must press OK 2x



press the End button to stop deleting and return the handset to standby mode

7.4 TO VIEW CONTACTS:

You can check the number and the set ringtone for each contact as follows:

2x ↔/OK -? use the A and V buttons to select the desired contact press the OK button ⇒/0K -? use the \blacktriangle and \checkmark buttons to select the option [VIEW] press the OK button ⇒/OK now use the ▲ and ▼ buttons to view the name, number *****? and set ringtone for the selected contact press the OK button -⇒/ок press the End button to stop viewing and return the 6 handset to standby mode

7.5 MEMORY STATUS:

You can check the memory status of your handset as follows:

3x press 3x the

button * use the ▲ and ▼ buttons to select the option [PB STATUS] press the OK button ⊕/OK the display will now show how many of the available Ψ 50 memories you're currently using (the example below shows that 23 of the 50 are being used) press 3x the End button to stop viewing and return the 3x handset to standby mode Θ


7.6 AVAILABLE CHARACTERS:

While programming the names of your contact, you can use the following available characters:

toets:	x 1x	indrul 2x	kken: 3x	4x	5x	6x
1	sp	-	1	(s	o = sp	oatie)
2	Â	В	С	2		
3	D	Е	F	3		
2 3 4	G	Н	1	4		
5	J	Κ	L	5		
6	М	Ν	0	6		
7	Р	Q	R	S	7	
8	Т	U	V	8		
9	W	Х	Y	Ζ	9	
0	0					
*	*	?	/	1	()
#	#	ŕ	,	-		&

7.7 LINK MEMORIES TO DIALBUTTONS:

A contact from the memory can be assigned to each of the 2-9 buttons. Whit the handset in standby mode, you can then press and hold that button for at least 2 seconds to automatically dial the assigned number.





press the OK button



press 3x the End button to stop assigning and return the handset to standby mode



to assign, edit or delete: press 3x the ⇒ button



use the ▲ and ▼ buttons to select the option [DIRECT MEM.]



press the OK button



use the \blacktriangle and \checkmark buttons to select the desired button (2~9)



press 2x the OK button




use the ▲ and ▼ buttons to select the option [DELETE] to remove the assigned contact or select [EDIT] to assign a different contact to the selected button



press the OK button to confirm deleting the contact or assigning another contact

7.8 M1 & M2:

The direct memory keys M1 and M2 are suitable for numbers you want to dial frequently. These are for numbers only, no name.




8 INTERCOM, TRANSFER AND CONFERENCE

8.1 INTRODUCTION:

You can register up to 5 handsets on the PDX-2608 / PDX-2608 DUO base station. When registering multiple handsets, you can make internal calls free of charge and you may transfer calls. If your telephone was supplied with multiple handsets, you can immediately start using these functions. If your telephone was supplied with only one handset, you can purchase additional handsets that must be registered on the base first. See paragraph 13.2 for instructions.


8.2 INTERCOM:






* When receiving an external call during an intercom call, the handset will emit notification tones. Disconnect your intercom call, wait until the usual ringtone sounds and answer the outside call (when using more than 2 handsets, you can also accept the outside line using any free handset).

8.3 TRANSFER / CONFERENCE CALL:





9 CLOCK & ALARM (WAKE-UP) FUNCTION

9.1 INTRODUCTION:

In standby mode, the display of the handset(s) shows the time. Moreover, you can program an alarm or wake-up time (for each handset).

9.2 TIME AND DATE SETUP:

€/ОК	press the
	use the \blacktriangle and \blacktriangledown buttons to select the option [DATE & TIME]
⊘/OK	press the OK button
	use the \blacktriangle and \checkmark buttons to choose one of the following options:
¥ Jate format	[DATE FORMAT] select this option to set the time display format: day-month-year or month-day-year
¥ TTMF F∏RMAT	[TIME FORMAT] use this option to switch between the 12-hour or 24- hour clock. <i>For example at quarter past nine in the</i> <i>evening:</i> 12-hour clock: 9:15 PM / 24-hour clock: 21:15



[SET TIME] here you can set the time

[SET DATE] here you can set the date

9.3 TO ENABLE/DISABLE THE ALARM AND TO SET THE ALARM TIME:

use the \blacktriangle and \checkmark buttons to select the option [ALARM]



2?

⇒/OK

press the OK button



use the \blacktriangle and \checkmark buttons to switch the alarm ON or OFF



use the keypad to enter the desired alarm time



press the ok button



the display will show the word [SNOOZE]



press the OK button



now use the \blacktriangle and \checkmark buttons to enable or disable the snooze function (see below an explanation of the snooze function)



press the OK button to save your settings and press the End button to return the handset to standby mode

9.4 ALARM OPERATION:



- the symbol appears in the display when the wakeup signal is enabled
- at the set time, the alarm will sound for 45 seconds or until you press a random button to stop the alarm signal beforehand
- when the [snooze] function is enabled and you press a random button to stop the alarm signal, the alarm will sound again after 7 minutes; you can disable an enabled snooze function by pressing and holding the End button for at least 5 seconds while the alarm sounds (or by disabling the alarm function according to the instructions in the previous paragraph)
- the alarm is not repeated daily
- the alarm volume is the same as the set ring volume; if the ring volume is set to 0 (off), the alarm signal is set to volume level 1

10 HANDSET PREFERENCES

10.1 INTRODUCTION:

You can use the menu [HS SETTINGS] to adjust various handset settings to your personal preferences.

10.2 MENU FOR HANDSET PREFERENCES:

-⇒/OK ***** ⇒/OK **A**

press the \Rightarrow button

use the \blacktriangle and \checkmark buttons to select the option [HS SETTINGS]



press the ok button

now use the ▲ and ▼ buttons to choose from the following options:

[RING SETUP]

Here you can set the ringtone signals. Keep in mind that you can set different signals for internal calls and for outside calls. You can also choose to turn the ring volume off, in this case the **x** symbol will appear in the display

[TONE SETUP]

- Key tone:

Here you can enable or disable the following tones:

the tones that are emitted when pressing buttons

- Battery tone weak: the tones that are emitted when the batteries are nearly empty
- Out of range: the tones that are emitted when the handset is nearly out of range from the base station

[EQUALIZER]

You can use the equalizer to (extra) amplify the treble or bass levels. This tone control is disabled when set to 'natural'

[SELECT BASE]

When the handset is registered to multiple base stations, than use this menu option to link the handset to the prefered base station.

[LANGUAGE]

Here you can set the language in which the various messages are displayed on the display.

You can restore a known language as follows in case you've set an unknown language accidentally:

- 1. press: ⇒ ▼ ▼ ▼ OK ▼ ▼ ▼ ▼ OK
- 2. now use ▲ and ▼ to select the desired language
- 3. press OK to confirm

[RENAME HS]

Use this option to assign a personal name to the handset of up to 10 characters. Use the ${f C}$ button to delete the old name.

See paragraph 7.7 for all available characters.

[HS DISPLAY]

Here you can determine whether the handset name or actual time must be shown with the handset in standby mode.

[AUTO ANSWER]

Here you can determine whether an incoming call can be answered directly by picking up the receiver from the base or charger. With this function disabled, you must always press the Call button to accept incoming calls.

BASE PREFERENCES 11

11.1 INTRODUCTION:

Via the menu [BS SETTINGS] you can, amongst others, deregister other handsets, adjust the FLASH interruption time and change your PIN code.

11.2 MENU FOR BASIS PREFERENCES:

⇒/ok -? ⇒/ok **A 2**?

press the \Rightarrow button

use the \blacktriangle and \checkmark buttons to select the option [BS SETTINGS]



press the ok button

use the \blacktriangle and \checkmark buttons to choose from the following options:

[DELETE HS]

Here you may deregister faulty or lost handset. Keep in mind that you can only deregister other handsets, you cannot deregister your own handset. See also paragraph 13.4.

[FLASH TIME]

Here you can set the interruption duration of the flash pulse (see also paragraph 3.8):

- short setting: 100mS
- average setting: 270mS
- long setting: 600mS

Ask your telephone service provider or the supplier of your home or office switchboard for the most suitable interruption time. The default flash time of 100 mS is used in the Benelux, which is already set upon leaving the factory.

[CHANGE PIN]

A PIN code is required for various settings and for registering and deregistering handsets. The stand factory PIN code is 0000, but you can use this menu to change this PIN code into your personal 4-digit PIN code.

- 1. make sure the display shows [CHANGE PIN]
- 2. press 2x the OK button
- 3. now first enter the old PIN code
- 4. press 2x the OK button
- 5. enter the new PIN code
- 6. press 2x the OK button
- 7. enter the new PIN code again
- 8. press 1x the OK button
- 9. you'll hear a confirmation tone; the new PIN code is now stored

Instructions to restore the default factory PIN code 0000 in case you've forgotten or lost your personal PIN code:

- 1. remove the power adaptor of the base from the wall socket
- on the base, press the ●)) button AND KEEP THIS BUTTON DE-PRESSED
- now insert the adaptor back into the wall socket (keep the •)) button depressed)
- 4. after <u>5 seconds</u>, release the ») button
- 5. the PIN-code is now changed back into 0000

12 RESETTING PREFERENCES

12.1 INTRODUCTION:

Via the menu [DEAFAULT], you can reset your settings to the standard factory settings.

12.2 MENU FOR RESETTING PREFERENCES:



use the ▲ and ▼ buttons to select the option [DEFAULT]

press the OK button

use the keypad to enter the PIN code

press 2x the OK button

12.3 FACTORY SETTINGS:

Name handset Display language Internal ringtone External ringtone Ring volume Receiver volume Hands-free volume Battery tone Out-of-range tone Key tones	HANDSET Dutch Melody 2 Melody 1 Level 3 Level 3 Level 3 Enabled Enabled Enabled	Auto answer Clock format Date/time Flash: Voicemail indication: PIN code: Last dialled memory: Caller-ID memory: Phonebook memory:	0000 empty empty
---	--	--	------------------------


13 ADDITIONAL HANDSETS

13.1 INTRODUCTION:

You can connect 5 handsets with each base station from the PDX-2608 / PDX-2608 DUO series. This way you can make internal calls free of charge and you can also transfer calls.

13.2 TO REGISTER HANDSETS:

Attention, the handset(s) supplied with the basis is (are) already registered to that base. The following instructions are only valid for registering new handsets or for re-registering handsets in case of a power outage.



After several seconds the base and handset will have 'found' each other and the display of the handset will show the internal number of that handset (1-5); the handset is now registered

13.3 TIPS FOR MULTIPLE HANDSETS:

- Instructions for dialling and incoming calls are identical for all handsets of the PDX-2608 / PDX-2608 DUO series.
- Intercom calls are free of charge.
- When receiving an external call during an intercom call, the handsets will emit a notification tone. Disconnect the internal call, wait for the regular ringtone to sound and answer the external call. In case you've registered more than 2 handsets on the base, you can also answer the outside call using any free handset.
- When an outside call is being received, all handsets will start ringing. The handset that's the first to answer the call will be connected with the outside line.

13.4 DE-REGISTERING HANDSETS:

Defect or lost handsets must be de-registered:

- 1. press the \Rightarrow button
- 2. use the ▲ and ▼ buttons to select the [BS SETTINGS] option
- 3. press the OK button
- 4. use the ▲ and ▼ buttons to select the [DELETE HS] option
- 5. press the OK button
- 6. use the keypad to enter the PIN code
- 7. press the ok button
- 8. use the \blacktriangle and \checkmark buttons to select the handset you want to deregister
- 9. press the ok button

Keep in mind that you can only deregister other handsets; you cannot deregister your own handset.

14 TIPS AND WARNINGS

14.1 GENERAL:

- Read the user manual carefully and follow all instructions.
- Never place or use the phone in a wet or moist room or environment.
- Take care of proper heat dissipation; never cover the phone and/or the power supply adapter(s), and do not place them directly beside a heat source.
- Use only the included adapter(s); connecting another type of adapter may cause damage to the electronics.
- Take care that the cable of the phone and the adapter do not get damaged, and prevent that they cause tripping or falling.
- Never disassemble the phone and the adapter(s); this may only be done by qualified personnel.

14.2 INSTALLATION:

- Connect or disconnect the cables of the phone and the power supply adapter only to the base station when the power supply adapter has been unplugged from the mains socket, and the phone connector has been disconnected from the phone socket.
- Do not install the phone during a lightning storm.
- Do not install a phone connection point in a wet or moist environment.
- Do not touch uninsulated phone or adapter cables, unless they are disconnected from the phone network or the mains power.

14.3 PLACEMENT:

• Preferably, do not place the device on surfaces that have been treated with cellulose; the rubber feet can leave traces on these.

• Do not place the phone in the direct vicinity of other phones or other electronic (medical) devices, TL tubes and other gas discharge lamps; the emitted radio waves of these (and other) wireless phone(s) may disrupt the functioning of the equipment, or the emitted signals of the equipment disrupt the functioning of the phone.

14.4 RANGE:

14.5 POWER SUPPLY HANDSET:

- The display of the handset is provided with a built-in battery capacity meter (III). When the battery symbol is full, the batteries are charged; when the battery symbol is empty or only half full, the batteries should be recharged.
- For optimal use, we recommend you to place the handset onto the charger every evening. This does not have an adverse effect on the rechargeable batteries.

14.6 HEARING AIDS:

• Users of older generation hearing aids always shall keep into account a possible uncomfortable buzzing tone when using DECT phones.

14.7 MEDICAL EQUIPMENT:

• It is possible that enabled DECT phones interfere with sensitive medical equipment. When the phone is kept in the vicinity of the medical device, interference can occur. Do not place a DECT phone on or near a medical device, not even when it is in standby mode.

14.8 POWER FAILURE:

• This phone obtains its power supply from the mains power. In case of failure of the mains power, this phone cannot be used.

14.9 EAVESDROPPING:

• Eavesdropping on a DECT phone is virtually impossible. Not only shall one be within reach of the DECT phone, one also needs expensive equipment.

14.10 MAINTENANCE:

- Clean the phone only with a moist cloth; do not use any chemical detergents.
- The adapter and the phone cable shall be disconnected before cleaning.

14.11 ENVIRONMENT:

- The packaging of this telephone can be collected as old paper. However, we recommend you to save it, to adequately protect the phone during transport.
- When replacing this telephone, please return it to the supplier to ensure environment-friendly processing
- Exhausted batteries may never be disposed of in household waste but must be handed in at your local depot for chemical waste.

15 POSSIBLE PROBLEMS AND SOLUTIONS

15.1 POSSIBLE PROBLEMS AND SOLUTIONS

- No dialling tone.
 - The outside line is being used by another unit. Wait until that call has ended and try again.
 - Check the connection between the base and you telephone socket (when in doubt, connect a different phone to your telephone socket).
- The power supply is interrupted.
 - Check whether the adaptor below at the rear of the base is plugged in and that the power adaptor is connected with a wall socket.

15.2 PROBLEMS WITH INCOMING CALLS:

- No notification of incoming calls:
 - The bell is disabled; enable it.
 - Check the connection between the phone and your telephone socket (when in doubt, connect a different phone to your telephone socket)
- You are continuously busy:
 - Check whether you have a 2nd telephone with the receiver next to it.
 - Check whether another handset registered on your telephone is keeping the line busy.
 - Connect another phone to your phone connection, and use this to check whether the malfunction originates from your connection or your carrier.
- Handset switches itself off when it starts ringing:
 - The batteries cannot supply power for the ringtone. Clean the battery contacts or replace the batteries.

15.3 PROBLEMS DURING CALLING:

- Beep tones during an intercom call:
 - You are called from outside during an intercom call; end this call, wait until the phone rings normally and answer the call.
- Beep tones during a call:
 - The batteries are nearly empty; disconnect the call and replace the handset onto the base or charger to recharge the batteries
- Noise and other distortions:
 - You are getting out of reach of the base station; reduce the distance.
 - There are other electrical devices in the vicinity that interfere with the radio waves of your phone; try another location.

15.4 PROBLEMS WITH CALLER IDENTIFICATION:

- You do not receive Name or Caller Identification information on the display:
 - Check whether your carrier transmits these signals (you shall subscribe to this service with some telephone companies).
- You do receive the numbers on the display of your phone, but not the name.
 - The carrier does not forward names; consult your carrier for this.
 - The name has not been programmed in the memory of your phone; program it. (see paragraph 7.3)

15.5 OTHER:

- The display stays blank:
 - The batteries are empty, please recharge them
- The handset does not have contact with the base station:
 - You are too far from the base station; reduce the distance.
 - The base station has been switched off. Check and repair it.
 - The handset is not registered with the base station (anymore); register it (again). (see paragraph 13.2)

In case the failure has not been solved with aforementioned solutions:

- Remove the batteries from the handset, and unplug the power supply adapter and the phone connector from their sockets; connect everything again after several minutes.
- You can also contact the Profoon service center or the supplier of this phone.

16 DECLARATION OF CONFORMITY

This device complies with the essential requirements and provisions as described in the European Directive 2014/53/EU.

The declaration of conformity is available at: http://DOC.hesdo.com/PDX-2608-DOC.pdf

17 SPECIFICATIONS

Protocol:	DECT / GAP, 5 handsets
Phone book:	20 names and number
Call history:	DTMF & FSK, 10 memories
Last number memory:	5 numbers
Dialling:	TONE (DTMF)
FLASH :	100, 270 & 600 ms, adjustable.
Boost amplification:	+8dB
Power supply charger:	2x 1.2V NiMH batteries, 500mAh, format AAA
Power supply base station:	6 VDC, 300 mA, - (+
Range:	50 m indoors, 300 m outdoors
Operational life (with full bat	teries):
	standby: > 100 hours
	use: > 10 hours
Connection factor:	12.5 (according to the old method, this
	corresponds with a connection factor of 0.5)
Operational temperature:	15°C to 40°C
Storage temperature:	-20°C to 60°C
Frequency Range:	1880-1900 Mhz
Maximum Power:	< 24 dBm

18 TABLE OF CONTENTS

1 OVERVIEWS

1.1	HANDSET	.2
1.2	DISPLAY	.4
1.3	BASE	.5

2 INSTALLATION

2.1	BASE STATION	6
2.2	HANDSET	7
2.3	EXTRA HANDSETS AND CHARGERS	7

3 3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9 3.10	CALLINGRECEIVING CALLS8CALLING WITH THE PHONE OR8USING THE HANDS-FREE FUNCTION8ENDING CALLS8DIALLING NUMBERS9TO MUTE THE MICROPHONE11RECEPTION VOLUME11CALL DURATION12R/FLASH FUNCTION12HANDSET SEARCH FUNCTION12TO SWITCH OFF THE HANDSET13
4 4.1 4.2 4.3	RE-DIALLING INTRODUCTION14TO REDIAL14TO SAVE OR DELETE14
5 5.1 5.2 5.3 5.4 5.5	CALLER IDENTIFICATIONINTRODUCTION16INDICATION NEW CALLS16VIEW MEMORY AND CALLBACK16DETAILS, SAVE OR DELETE17ADDITIONAL INFORMATION18
6 6.1 6.2	VOICEMAIL INDICATION 19 INTRODUCTION 19 NEW VOICEMAIL INDICATION 19
7 7.1 7.2 7.3	PHONE BOOK MEMORY20INTRODUCTION20SEARCHING FOR AND CALLING CONTACTS20TO ADD, EDIT OR DELETE CONTACTS21

7.4 7.5 7.6 7.7 7.8	TO VIEW CONTACTS MEMORY STATUS AVAILABLE CHARACTERS LINK MEMORIES TO DIALBUTTONS M1 & M2	25 25 26
8 8.1 8.2 8.3	INTERCOM, TRANSFER AND CONFERENCE INTRODUCTION INTERCOM TRANSFER / CONFERENCE CALL	29
9 9.1 9.2 9.3 9.4	CLOCK & ALARM (WAKE-UP) FUNCTION INTRODUCTION TIME AND DATE SETUP TO ENABLE/DISABLE THE ALARM AND TO SET THE ALARM TIME ALARM OPERATION	
10 10.1 10.2	HANDSET PREFERENCES INTRODUCTION MENU FOR HANDSET PREFERENCES	
11 11.1 11.2	BASE PREFERENCES INTRODUCTION MENU FOR BASIS PREFERENCES	
12 12.1 12.2 12.3	RESETTING PREFERENCES INTRODUCTION MENU FOR RESETTING PREFERENCES FACTORY SETTINGS.	

13	ADDITIONAL HANDSETS	
13.1	INTRODUCTION	
13.2		
13.3	TIPS FOR MULTIPLE HANDSETS	
13.4	DE-REGISTERING HANDSETS	41
14	TIPS AND WARNINGS	
14.1	PLACEMENT	
14.2	RANGE	
14.3	POWER SUPPLY HANDSET	43
14.4	HEARING AIDS	44
14.5	MEDICAL EQUIPMENT	44
14.6	POWER FAILURE	44
14.7	EAVESDROPPING	
15	POSSIBLE PROBLEMS AND SOLUTIONS	
15.1	PROBLEMS DURING CALLING	
15.2	PROBLEMS WITH INCOMING CALLS	
15.3	PROBLEMS DURING CALLING	
15.4	PROBLEMS WITH CALLER IDENTIFICATION	
15.5	OTHER	
16	SPECIFICATIONS	46

47		0
17	DECLARATION OF CONFORMITY4	0
17	TABLE OF CONTENTS4	17
19	WARRANTY5	52

19 WARRANTY

For the Profoon PDX-2808 / PDX-2808 DUO DECT you have a warranty of 24 months from the date of purchase. During this period, we guarantee the free repair of defects caused by material and workmanship errors. All this subjected to the final assessment of the importer.

HOW TO HANDLE: If you notice any defect, first refer to the user's manual. If the manual provides no definite answer, please contact the supplier of this telephone or contact customer service of Profoon.

THE WARRANTY BECOMES NULL AND VOID: In case of improper use, incorrect connections, leaking and/or incorrectly installed batteries, use of unoriginal parts or accessories, negligence and in case of defects caused by moisture, fire, flooding, lightning and natural disasters. In case of unauthorised modifications and/or repairs performed by third parties. In case of incorrect transportation of the device without adequate packaging and when the device is not accompanied by this warranty card and proof of purchase.

The warranty does not cover connecting cables, plugs and batteries. All further liability, especially concerning any consequential damages, is excluded.

