G9 BULB 170LM 2W 4000K NON-DIMM 285 BEAM CLEAR INTEGRAL

ILG9NE008



Integral LED G9 lamps run at less than 2W and offer a lifetime of thousands of hours more than their halogen equivalents. This makes them an ideal retrofit for existing G4 fittings.

Details

| Quick Order Code: Barcode: Category: Range Name: Product Type: Market Segment: Warranty (Years): CE RoHS: | 213488 5055788224631 Lamps G9 G9 Commercial indoor, Residential indoor 2 Yes |
|--|---|
| Physical Data | |
| Product Length (mm): | 48 |
| Product Width (mm): | 16 |
| Product Weight (g): | 5.2 |
| Material: | Polycarbonate |
| Base Term: | G9 |
| Bulb Base: | G9 |
| Construction: | Polycarbonate |
| Globe Finish: | Clear |
| Bulb Fixing: | Pendant, Wall, Desktop |
| Bulb or Luminaire Shape: | Oval |
| Placement / Application: | Indoor, General Lighting |
| Electrical Data | |

| Power (W): | 2 |
|-------------------------|--------------|
| Power Consumption (w): | 2 |
| Power Factor: | 0.9 |
| Wattage equivalent (W): | 20 |
| Amperage (mA): | 160 |
| Dimming: | Non-Dimmable |
| Driver Included: | Yes |

| Electric | Current: |
|----------|----------|
| EN: | |


AC EN 61547:2009

Light Data

| Luminous Flux in Lumens (Im): | 170 |
|--|--------------------|
| Luminous efficacy (Im/W): | 85 |
| Correlated Colour Temperature (CCT) (K): | 4000 |
| Colour Temperature: | 4000K - Cool White |
| Colour Temperature Name: | Cool White |
| Beam Angle: | 285 |
| Colour Rendering Index (CRI): | 80 |
| Frequency Range (Hz): | 50/60 |
| Instant on (Less than 1 second): | Yes |
| LED Type: | COB |
| Lifetime (hours): | 15000 |
| Switching Cycles: | 7500 |

Environment

| EN: | EN 61547:2009 |
|-------------------------------------|---------------|
| CE RoHS: | Yes |
| Previous Energy Rating: | A++ |
| New Energy Rating: | F |
| Hg 0% (Mercury Free): | Yes |
| IP Rating (Ingress Protection): | IP20 |
| Lowest Operating Temperature (°C): | -20 |
| Maximum Operating Temperature (°C): | 40 |



Packaging

| Package Weight (g): | 5.5 |
|----------------------|-------------------------|
| Package Length (mm): | 55 |
| Package Width (mm): | 20 |
| Package Depth (mm): | 20 |
| | Portal.integral-led.com |