

## P/N: CM44

### Copyright

© 2019, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: CM44

Commit: 61657

Language: en-US

Modified: 2019-12-05

Formatted: 2019-12-05

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



General description	
Part number	CM44
Part name	Professional 400A TRMS AC Clamp Meter + Type K
<p>The FLIR CM44 Clamp Meter is a professional and affordable true RMS meter designed for commercial and residential electricians. The FLIR CM44 features AC clamp measurement to meet your unique needs. The meter is equipped with a bright backlit display for ease of use inside electrical panels. Accu-Tip technology delivers amperage measurements on smaller-gauged wires more accurately—to a 10th of a digit. It offers MAX/MIN/AVG recording, frequency measurement, and electrical field detection to help you determine voltage presence and relative strength of the field. Made with an over-molded, easy-to-grip design, the FLIR CM44 clamp meter is durable enough to withstand a 2 m drop, and the slim form factor is convenient to carry in your toolbox anywhere you go.</p>	
<p>Professional performance at an affordable price:</p> <ul style="list-style-type: none"> <li>Operates at -10 to 50°C (14–122°F).</li> <li>Built to accept up to a 30 mm conductor.</li> <li>True RMS measurements.</li> </ul>	
<p>Features: DC voltage, AC voltage (digital low-pass filter/VFD), clamp-on AC current, Accu-Tip clamp-on AC current, frequency, resistance, capacitance, diode, DC <math>\mu</math>A, temperature.</p>	
Electrical measurement	
True RMS voltage	Yes
Auto-ranging	Yes
DC V range	600.0 V
DC V accuracy	$\pm 1.0\%$ + 5 digits
AC V range with digital low-pass filter	600.0 V
AC V range with digital low-pass filter: accuracy	$\pm 1.0\%$ + 5 digits (50–60 Hz)
Peak RMS inrush current (AC V and AC A)	
Response	80 ms to >90%
Resistance range	600.0 $\Omega$ , 6.000 k $\Omega$ , 60.00 k $\Omega$
Resistance	$\pm 1.0\%$ + 5 digits
Continuity	600.0 $\Omega \pm 1.0\%$ + 5 digits
Diode	2.000 V $\pm 1.5\%$ + 5 digits

**P/N: CM44**

© 2019, FLIR Systems, Inc.

#CM44; r. 61657; en-US

<b>Electrical measurement</b>	
Capacitance	200.0 $\mu$ F, 2500 $\mu$ F $\pm$ 2.0% + 4 digits <sup>1</sup>
DC $\mu$ A	200.0 $\mu$ A, 2000 $\mu$ A
DC $\mu$ A accuracy (burden voltage)	$\pm$ 1.0% + 5 digits (3.5 mV/ $\mu$ A)
<b>Temperature</b>	
Range <sup>2</sup> , accuracy <sup>3</sup>	-40.0 to 99.9°C, $\pm$ 1.0% + 1°C
Range <sup>2</sup> , accuracy <sup>3</sup>	100-400°C, $\pm$ 1.0% + 1°C
Range <sup>2</sup> , accuracy <sup>3</sup>	-40 to 99.9°F, $\pm$ 1.0% + 2°F
Range <sup>2</sup> , accuracy <sup>3</sup>	100-752°F, $\pm$ 1.0% + 2°F
<b>Low-current Accu-Tip clamp-on AC A</b>	
Range (50-60 Hz)	60.00 A
Accuracy <sup>4567</sup> (50-60 Hz)	$\pm$ 2.% + 5 digits
<b>Standard clamp-on AC A</b>	
Range (50 Hz~60 Hz)	60.00 A, 400.0 A
Accuracy <sup>891011</sup> (50-60 Hz)	$\pm$ 2.0% + 5 digits
Range (60-400 Hz)	60.00 A, 400.0 A
Accuracy <sup>891011</sup> (60-400 Hz)	$\pm$ 3.0% + 5 digits
<b>Line level frequency</b>	
Function (5.00-999.9 Hz)	600 V
Sensitivity <sup>12</sup> (Sine RMS) (5.00-999.9 Hz)	50 V
Function (50.00 Hz~400.0 Hz)	60 A (low-current mode)
Sensitivity <sup>12</sup> (Sine RMS) (50.00-400.0 Hz)	40 A
Function (50.00 Hz~400.0 Hz)	60 A, 400 A
Sensitivity <sup>12</sup> (Sine RMS) (50.00-400.0 Hz)	40 A
Accuracy	1% + 5 digits
<b>Non-Contact EF Voltage Detection</b>	
Typical voltage (tolerance: 10-36 V)	20 V
Bar graph indication	-

1. Accuracy specified for film capacitors or better.
2. Supplied thermocouple is rated for -20 to 250°C (-4 to 482°F) only, and therefore not rated for the entire specified temperature range of the meter.
3. K-type thermocouple range and accuracy not included. Accuracies assume the meter interior has the same temperature as the ambient temperature for correct junction voltage compensation. Allow adequate time for stabilization for significant changes of ambient temperature. Up to an hour, for changes >5°C (9°F), may be required.
4. Induced error from adjacent current-carrying conductor <0.06 A/A.
5. Specified with relative/DC zero mode applied to offset non-zero residual readings.
6. Add 10 digits to the specified accuracy at <4nA.
7. Position the conductor at the center of the Accu-Tip area. Conductor size must not exceed 8.8mm.
8. Induced error from an adjacent current-carrying conductor is <0.06 A/A.
9. Specified accuracy is for measurement made at the jaw center. When the conductor is not positioned at the jaw center, add 2% to the specified accuracy for position errors.
10. Add 10 digits to the specified accuracy at <6 A.
11. Add 3% to the accuracy specification for a crest factor of between 1.0 and 2.0. If the crest factor is >2.0, the reading may not meet specified tolerances.
12. DC bias, if any, not more than 50% of sine RMS.

**P/N: CM44**

© 2019, FLIR Systems, Inc.

#CM44; r. 61657; en-US

<b>Non-Contact EF Voltage Detection</b>	
Typical voltage (tolerance: 23–83 V)	55 V
Bar graph indication	--
Typical voltage (tolerance: 59–165 V)	110 V
Bar graph indication	---
Typical voltage (tolerance: 124–330 V)	220 V
Bar graph indication	----
Typical voltage (tolerance: 250–600 V)	440 V
Bar graph indication	-----
Indication	Number of bar graph segments and audible beep tones proportional to the detected field strength
Detection frequency	50/60 Hz
Detector:	Located inside the top of the stationary jaw
Additional measurement functions	Data hold, MIN/MAX/AVG, backlit LCD, 80 ms peak RMS inrush current mode, relative/DC zero
<b>General</b>	
Jaw opening	30 mm (1.2 in.) maximum
Display counts	6000
Measuring rate	5 times per second nominal
Calibration cycle	1 year calibration cycle recommended
Auto power off	32 minutes of inactivity
Power source	2 × 1.5 V AAA alkaline batteries
<b>Environmental data</b>	
Operational temperature	–10 to +50°C (14–122°F) (non-condensing) 10–30°C (50–86°F) (≤80% relative humidity (RH)) 30–40°C (86–104°F) (≤75% RH) 40–50°C (104–122°F) (≤45% RH)
Storage temperature	–20 to +60°C (4–140°F)
Relative humidity	80% maximum RH up to 31°C (88°F) decreasing linearly to 50% maximum RH at 50°C (122°F)
Temperature coefficient	0.15 × (specified accuracy)/°C, @ 0°C (32°F) to 18°C (64.4°F) or 28°C (82.4°F) to 50°C (122°F), or as otherwise specified
Operating altitude	2000 m (6562 ft.) maximum
Pollution degree	2
<b>Physical data</b>	
Dimensions (L × W × H)	217 mm × 76 mm × 37 mm (8.5 in. × 3.0 in. × 1.5 in.)
Weight	186 g (6.6 oz.)
<b>Warranty</b>	
Warranty	<a href="https://www.flir.com/testwarranty">https://www.flir.com/testwarranty</a>
<b>Certifications</b>	
Certifications	CE, cULus
Safety category rating	EN 61010-1 CAT IV—300 V, CAT III—600 V, EN 61010-2-032



## CM44

**P/N: CM44**

© 2019, FLIR Systems, Inc.

#CM44; r. 61657; en-US

Shipping information	
Packaging type	Retail color box
Packaging contents	CM4x, 2 x AAA batteries, premium CAT IV silicone test leads, type-K thermocouple, FLIR carrying pouch, quick start guide, warranty registration card
Packaging weight	0.8 kg (1.8 lb.)
Packaging dimensions (H x W x L)	33 cm x 14 cm x 10.7 cm (13 in. x 5.5 in. x 4.3 in.)
Master carton weight	10.6 kg (23.4 lb.)
Master carton dimensions (H x W x L)	62.3 cm x 29.3 cm x 36.1 cm (24.6 in. x 11.6 in. x 14.3 in.)
Master carton quantity	12
UPC	793950370445
EAN	0793950370445
Country of origin	Taiwan
Tariff code	9030.31.0000
Technical support	
Website	<a href="http://support.flir.com">http://support.flir.com</a>

**Supplies & accessories:**

- TA03-KIT; NiMH Rechargeable Battery Kit
- TA15; Universal Soft Sided Case
- TA55; AC Current Line splitter
- TA60; Thermocouple probe with adapter
- TA70; CAT IV Insulated Alligator Probes
- TA80; CAT IV Silicone Test Leads