



NOTE:

1. MATERIAL
- 1.1 CABLE: 26AWG BC*4+BRAID SHIELD(16/5/0.12ALM)+LSZH JACKET
CABLE MARKING:LogiLink S/FTP CAT6A 26AWG*4P P1MF PATCH ISO/IEC 11801 & EN 50173 VERIFIED HALOGEN FREE
 - 1.2 CONNECTER: RJ45(8P8C) MALE CAT6 TYPE, WITH SHIELD INSULATION: CLEAR BLUE POLYESTER CONTACTS:BRASS, GOLD PLATED 3u' SHIELD: STEEL, NICKEL PLATED.
 - 1.3 PVC MOLDING: PVC
 - 1.4 ALL COMPONENTS ARE ROHS COMPLIANT.
2. ELECTRICAL
 - 2.1 100% OPEN AND SHORT TEST



SECTION A-A



Length	Tolerance	CQ3xx1S	white
≤1000mm	±30mm	CQ3xx2S	grey
1000<L≤5000mm	±50mm	CQ3xx3S	black
5000<L≤10000mm	±100mm	CQ3xx4S	red
10000<L≤20000mm	±200mm	CQ3xx5S	green
20000mm<L	±500mm	CQ3xx6S	blue

LogiLink Professional

LogiLink
CAT.6A S/FTP Primeline 100% Copper

Approved by
PC13081401

Checked by
William

REV.	DESCRIPTION	DATE	ANGLE	REV.	SHEET	DWG. No. :	TITLE:	Design by
00	DESCRIPTION	2013-8-14	±3°	00	1/2	2D-PC13081401	26AWG SSTP CAT6A PATCH CABLE	PC13081401