


DS-KH8350-WTE1

Video Intercom Network Indoor Station

HIKVISION




reddot

Key Feature

- Premium tempered glass
- Aerospace-grade aluminum
- New UI V2.0: User friendly design
- 7-inch colorful touch screen with resolution 1024 × 600
- 8.6 mm Ultra-slim design
- Reddot award 2017 winner
- Standard PoE
- Support capture while video calling
- Remote unlocking via the client software or the mobile client
- Views live videos of door stations and linked cameras

Typical Application



Approval

CE-EMC	a. EN 55032:2015 b. EN 61000-3-2:2014 c. EN 61000-3-3:2013 d. EN 50130-4:2011 +A1:2014
CE-LVD	EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013
CE-RED	a. EN 201 489-1 V2.1.1, EN 301 489-17 V3.1.1 b. EN 300 328 V2.1.1, EN 62311:2008
CB	IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013
FCC-SDOC	47 CFR Part 15, Subpart B
FCC-ID	47 CFR Part 15, Subpart B
C-TICK(EMC)	AS/NZS CISPR 32:2015
C-TICK(RF)	AS/NZS 4268:2017
UL	UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07, Information Technology Equipment – Safety – Part 1: General Requirements
IC(EMC)	ICES-003:Issue 6
IC(RF)	RSS-247 Issue 2, February 2017, RSS-Gen Issue 5, April 2018
ROHS	2011/65/EU
REACH	Regulation (EC) No 1907/2006
WEEE	2012/19/EU

Specification

System parameters

Memory	128 MB
Flash	32 MB
Operation system	Embedded Linux operation system

Display parameters

Display screen	7-inch colorful IPS LCD
Display resolution	1024 × 600
Operation method	Capacitive touch screen, physical button

Audio parameters


Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio compression standard	G.711 U
Audio compression rate	64 Kbps
Audio quality	Noise suppression and echo cancellation

Network parameters



Wired network	10/100 Mbps self-adaptive
Wireless network	Wi-Fi 802.11 b/g/n
Network protocol	TCP/IP, SIP, RTSP
Network interface	1 RJ-45 10/100 Mbps self-adaptive
Alarm input	8-ch alarm inputs
I/O output	2
TF card	Max to 32 G, SD 2.0 or lower version
RS-485	Supported

General

Power supply	IEEE802.3af, standard PoE 12 VDC/1 A
Power supply via detector	12 V, 200 mA
Power consumption	≤ 7 W
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	10% to 90%
Dimensions	180 mm × 140 mm × 22.4 mm (7.09" × 5.51" × 0.88")
Weight	899 g (with packaging) 355 g (without packaging)
Certification	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE, UL,CB, RCM




Appearance and Interfaces



Accessory

Installation



Surface Mounting

Available Model

DS-KH8350-WTE1

Dimension



Distributed by

**HIKVISION®****Headquarters:**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5988
overseasbusness@hikvision.com

Hikvision USA
T +1-800-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8049-4213
salesau@hikvision.com

Hikvision India
T +91-22-29465200
sales.in@hikvision.com

Hikvision Canada
T +1-866-200-0500
sales.ca@hikvision.com

Hikvision Thailand
T +662-275-9948
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5507770
sales.eu@hikvision.com

Hikvision Italy
T +39-0458-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3338-0650
latam.support@hikvision.com

Hikvision Turkey
T +90 216521 7070 - 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7052-0413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01268-882140
sales.uk@hikvision.com

Hikvision South Africa
T +27 11 530 1172
sale.africa@hikvision.com

Hikvision France
T +33 01 30 50 40 00
info.fr@hikvision.com

Hikvision Kazakhstan
T +7 727-9739997
hik.kz@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-7432000
sales.ae@hikvision.com

Hikvision Singapore
T +65-6894-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-18-88
info.es@hikvision.com

Hikvision Tashkent
T +99-71-1238-0438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-253-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-959-87-88
ru@hikvision.com

Hikvision Korea
T +82-1031-771-8817
ko@korea@hikvision.com

Hikvision Poland
T +48-22-480-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com