

## Product Parameter

Material: ABS/ PP/ Hardware/ Electronic components  
Battery voltage: 3.7 V  
Battery capacity: 2000 mAh  
Input voltage/current: DC5 V/ 1000 mA  
Output power: 4 W  
Motor speed: Low speed: 4.6 V 2300 rpm  
Medium speed: 6.5 V 3100 rpm  
High speed: 8.3 V 3700 rpm  
Working current: Low speed: 290 mA;  
Medium speed: 510 mA  
High speed: 890 mA;  
Working power: Low speed: 1.1 W; Medium speed: 1.9 W  
High speed: 3.3 W;  
Product size: 104 • 115 • 370 mm  
Product weight: 307 g  
Standard: GB 4706.1-2005/GB 4706.27-2008  
Inspection: Qualified  
Place of origin: Shenzhen, China

材料: ABS/PP/五金/风扇控制线路板  
电池电压: 3.7V  
电池容量: 2000mAh  
输入电压/电流: DC5V/1000mA  
输出功率: 4W  
马达转速: 一档4.6V 2300转;  
二档6.5V 3100转; 三档8.3V 3700转  
工作电流: 一档290mA; 二档510mA;  
三档890mA  
工作功率: 一档1.1W; 二档1.9W; 三档3.3W  
产品尺寸: 104\*115\*370mm  
产品重量: 307g  
执行标准: GB 4706.1-2005/GB 4706.27-2008  
检验: 合格品  
产地: 中国·深圳



2 950009 043981

Evolize Portable Pow...ineblauw LVB



RoHS



MADE IN CHINA