

# EU Type-Examination Certificate

according to Regulation (EU) 2016/426 Article 14, section 2.  
on appliances burning gaseous fuels – Module B – production type

Certificate No.: GB 002875 001 PIN: 2806DL0030

Test Report No.: 31002856 001

Manufacturer: **Ttulpe B.V.**  
Wester Boekelweg 21a, 1718MJ Hoogwoud, Netherlands

Product: **Gas-fired instantaneous water heater (1401)**

Identification: **Models:**  
Indoor B-10 N20 Eco,  
Indoor B-10 N20-E Eco,  
Indoor B-10 N20/N25 Eco,  
Indoor B-10 B30/37/50 Eco,  
Indoor B-10 P30/37/50 Eco.

See details in Annex I

Tested according to: **EN 26:2015**

Countries of destination: **AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, GB, GR, HR, IE, IT, LT, LU, LV, NL, NO, PL, PT, RO, SE, SI, SK, TR**

Valid until: **17<sup>th</sup> Mar. 2031**

This EU type-examination certificate refers to the above-mentioned product. This is to certify that the test sample is in conformity with the essential requirements of Annex I of the Regulation. The Certificate holder / Manufacturer is entitled to use this certificate in connection with the EU declaration of conformity in accordance with the Regulation. This certificate does not imply assessment of the series production of the product. This certificate itself does not permit the affixing of CE marking followed by the identification number of the notified body.

## Certification Body

Date of issue:  
Budapest, 17<sup>th</sup> Mar. 2021

Tasn@di G@bor

Digitally signed by Tasn@di G@bor  
DN: cn=Tasn@di G@bor, gn=G@bor, c=HU, l=Dunakeszi  
o=CerTrust Ltd., e=gabor.tasnadi@certrust.eu  
Reason: I am the author of this document  
Location:  
Date: 2021-03-17 14:06+01:00

.....  
Gábor Tasnádi

The CE marking may be used if all relevant and effective EU directives are complied with.

## Annex I to certificate No. GB 002875 001

Page 1/1

PIN: 2806DL0030

### Technical specifications of the appliances

Product name	Gas-fired instantaneous water heater						
Model name	Indoor B-10 N20 Eco, Indoor B-10 N20-E Eco, Indoor B-10 N20/N25 Eco, Indoor B-10 B30/37/50 Eco, Indoor B-10 P30/37/50 Eco.						
Flue type	B <sub>11BS</sub>						
Flue connection	Female, connection diameter = 110 mm, length min./max. 0.5 m / 3 m						
Appliance category	I <sub>2H</sub>	I <sub>2E</sub>	I <sub>2EK</sub>	I <sub>3B/P</sub>	I <sub>3P</sub>	II <sub>2H3B/P</sub>	II <sub>2E3B/P</sub>
Reference gas	G20	G20	G20/G25.3	G30	G31	G20/G30	G20/G30
Gas pressure (mbar) (with governor)	20	20	20/25	29, 37, 50	30, 37, 50	20/29	20/29
Injector size (mm)	0.83&0.86		0.47&0.51		0.5&0.57	0.83&0.86/0.47&0.51	
Nominal heat input	20 kW						
Minimum heat input	7.5 kW		6.5 kW		7.5/6.5 kW		
Nominal heat output	18.3 kW						
Minimum heat output	6.7 kW		5.8 kW		6.7/5.8 kW		
Rated hot water production capacity	11 L/min ( Δt = 25 K )						
Electrical supply	1.5V DC supplied by battery type LR20						
Burner type	Water cooled low NOx gas burner						
Working water pressure (Pw)	0.1 bar - 10 bar						

Appliance category	Destination countries
I <sub>2H</sub>	AT, BG, CH, CY, CZ, DK, EE, ES, FI, GB, GR, HR, HU, IE, IT, LT, LU, LV, NO, PT, RO, SE, SI, SK, TR
I <sub>2E</sub>	DE, PL, RO
I <sub>2EK</sub>	NL
I <sub>3P</sub>	AT, CZ, DE, ES, FI, FR, GB, GR, NL, IE, IT, PT, RO, SI, SK
I <sub>3B/P</sub>	AT, BE, BG, CY, DE, DK, EE, FI, FR, GB, GR, HU, IT, LT, LU, LV, MT, NL, NO, PL, RO, SE, SI, TR
II <sub>2H3B/P</sub>	AT, CH, CY, CZ, DK, EE, FI, GR, HR, IT, LT, NO, RO, SE, SI, SK, TR
II <sub>2E3B/P</sub>	DE, PL, RO