



ELRO Item(s)	LF70-20-P	
Revision nr.	V3	
Material	300g carton board (grey bottom & white surface)	
Option 1		
Option 2	F corrugation in the core (middle)	
Option 3		
Size (mm)	140 (h) x 332 (w) x 110 (d)	
Contact	laurens.v@cossoconnects.eu	
Lot:	YXX = starting date of production Y = last digit of year / X = week nr. x 2 Production starts in 2018 week 2, lot number will be 804 / 8 = last digit of 2018 and / 04 = week 2 x 2	
Example		
Contact 1	demmy@green-king.cn	
Contact 2		



LF70-20-P_KMY0088-10W*2 EAN Pieces
 Consumer package 8719699349186 1
 Inner Carton 8719699349216
 Outer Carton 8719699349346



DUO LED FLOODLIGHT 20 WATT
MOTION SENSOR

Home is not a place, it's a feeling



- EN Energy efficient 2 x 10W high power LED 1200 lumen**
- PIR motion detector, 12m, 120°
 - Time and lux level can be adjusted
 - LED Panels can be adjusted separately
 - IP54 Waterproof

- DE Energieeffiziente 2 x 10W Hochleistungs-LED 1200 Lumen**
- PIR-Bewegungsmelder, 12m, 120°
 - Zeit und Lux Level können eingestellt werden
 - LED-Panelen separat einstellbar
 - IP54 Wasserdicht

- NL Energie-efficiënte 2 x 10W high power LED 1200 lumen**
- PIR bewegingsmelder, 12m, 120°
 - Tijd en lux-niveau instelbaar
 - LED-panels kunnen afzonderlijk worden afgesteld
 - IP54 waterdicht

- FR LED haute puissance 2 x 10W à haut rendement énergétique 1200 lumen**
- Détecteur de mouvement PIR, 12m, 120°.
 - Réglage de la durée et du niveau de lux
 - Les panneaux LED peuvent être réglés séparément
 - Étanchéité IP54



DUO LED FLOODLIGHT 20 WATT
MOTION SENSOR

EN SPECIFICATIONS	DE TECHNISCHE DATEN	NL SPECIFICATIE	FR SPECIFICATIONS	ELRO_LF70-20-P
Power	Leistung	Vermogen	Puissance	AC 220V-240V, 50Hz
Power Cord	Netzkabel	Stroomdraad	Cordon d'alimentation	H05RN-F, 3G, 0,75 mm ² x 90 cm
Lighting Load	Beleuchtungsbelastung	Verlichtingsbelasting	Charge d'éclairage	20W
Detection angle	Erfassungswinkel	Detectiehoek	Charge d'éclairage	120° (20°/RH85%) h 2 mtr.
Detection distance	Erkennungsabstand	Detectieafstand	Angle de détection	12 mtr. (20°/RH85%) h 2 mtr.
Working Temperature	Arbeitstemperatur	Werktemperatuur	Température de fonct.	-20°C ~ 40°C (95%RH max)
Mounting Height	Arbeitshöhe	Montagehoogte	Hauteur de montage	1,8 ~ 2,5m
Size/Weight	Größe / Gewicht	Formaat / Gewicht	Taille poids	33 x 14 cm / 510gr.
Lumen (lm)	Lumen (lm)	Lumen (lm)	Lumen (lm)	>1200 lm
Color Temperature(K)	Farbtemperatur (K)	Kleurtemperatuur (K)	Température de couleur (K)	6500K ± 250K
Life Span (hours)	Lebensdauer (Stunden)	Levensduur (uren)	Durée de vie (heures)	>18,000 (Hrs)
Protection Class	Schutzklasse	Beschermingsklasse	Classe de protection	Class II
Protection Degree	Schutzgrad	Beschermingsgraad	Degré de protection	IP54
Application	Anwendung	Toepassing	Application	Outdoors & Indoor Use

ELRO Europe | www.elro.eu
 Postbus 9007 - Box 1800
 1006 GC Amsterdam The Netherlands

