

*Printing date* 02.06.2015 *Version number* 53 *Revision:* 02.06.2015

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP CAR CARE TYRE SHINE
- · Article number: 000711
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Preparation
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

Fax: +31 (0)561 694411

e-mail info@nl.motipdupli.com

- · Further information obtainable from: QHSE Department
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h 17:00h)

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

X

Xi; Irritant

R38: Irritating to skin.

8

F+; Extremely flammable

R12: Extremely flammable.

N;

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

*R67:* Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Trade name: MOTIP CAR CARE TYRE SHINE

(Contd. of page 1)

#### · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

#### · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

07 GHS09

#### · Signal word Danger

#### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

Naphtha (petroleum), hydrotreated light

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

*H411 Toxic to aquatic life with long lasting effects.* 

#### · Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*P251* Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

#### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

(Contd. on page 3)

GB -

Trade name: MOTIP CAR CARE TYRE SHINE

CAS: 64742-49-0		ontd. of page 25-50%
CAS: 64/42-49-0 EC number: 927-510-4 Index number: 649-328-00-1 Reg.nr.: 01-2119475515-33-xxxx	N R51/53 R67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	25-30%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	Skin Irrit. 2, H315; STOT SE 3, H336  propane F+ R12 Flam. Gas 1, H220	12.5-20%
Reg.nr.: 01-2119486944-21-xxxx CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane    F + R12	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane  F+ R12 Flam. Gas 1, H220	5-10%
CAS: 64742-49-0 EC number: 920-750-0 Index number: 649-328-00-1 Reg.nr.: 01-2119473851-33-xxxx	Naphtha (petroleum), hydrotreated light  Xn R65  F R11 N R51/53  R66-67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	5-10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GB

Printing date 02.06.2015 Version number 53 Revision: 02.06.2015

Trade name: MOTIP CAR CARE TYRE SHINE

(Contd. of page 3)

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

#### 106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection: Not required.

(Contd. on page 5)

Trade name: MOTIP CAR CARE TYRE SHINE

(Contd. of page 4)

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

<b>SECTION</b>	9: Ph	ysical and	chemical	properties
----------------	-------	------------	----------	------------

	1.1 1.1 2
9.1 Information on basic physical an	nd chemical properties
General Information Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	< 0 °C (< 32 °F)
•	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 200 °C (> 392 °F)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.9 Vol %
Upper:	10.9 Vol %
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
· Density at 20 °C (68 °F):	0.6853 g/cm³ (5.719 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.

(Contd. on page 6)

Printing date 02.06.2015 Version number 53 Revision: 02.06.2015

Trade name: MOTIP CAR CARE TYRE SHINE

(Contd. of page 5)

· Solubility in / Miscibility with

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dvnamic: Not determined. Kinematic: Not determined.

· Solvent content:

Organic solvents: 86.0 % · EU-VOC: 589.4 g/l 86.00 % · EU-VOC in %:

· 9.2 Other information No further relevant information available.

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· <i>LD/LC50</i> 1	values releva	nt for classification:
64742-49-	0 Naphtha (p	petroleum), hydrotreated light
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50 / 4 h	>25200 mg/m3 (rat)
	LC50 / 4h	>2 mg/l (rat)
	LC50 / 96 h	2.5 mg/l (Leuciscus idus)
106-97-8 b	utane	
Inhalative	LC50 / 4 h	658000 mg/m3 (rat)
64742-49-	0 Naphtha (p	petroleum), hydrotreated light
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2800 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m3 (rat)
	LC50/4h	23.3 mg/l (rat)
Primary ir	ritant effect:	

- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: *Irritant* 

Trade name: MOTIP CAR CARE TYRE SHINE

(Contd. of page 6)

### SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxi	· Aquatic toxicity:		
64742-49-0	Naphtha (petroleum), hydrotreated light		
EC50 / 24 h	>10 mg/l (Daphnia magna)		
	>100 mg/l (fish)		
LC50 / 48 h	4924 mg/l (fish)		
LC50 / 96 h	2.5 mg/l (Pimephales promelas)		
64742-49-0	Naphtha (petroleum), hydrotreated light		
LC50	LC50 127-159 mg/l (Leuciscus idus)		

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	· European waste catalogue	
20 01 13*	solvents	
15 01 04	metallic packaging	

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
$\cdot ADR$	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· IMDG	AEROSOLS (Naphtha (petroleum), hydrotreated light),
	MARINE POLLUTANT
· IATA	AEROSOLS, flammable

- GB

Printing date 02.06.2015 Version number 53 Revision: 02.06.2015

Trade name: MOTIP CAR CARE TYRE SHINE

	(Contd. of pag
· 14.3 Transport hazard class(es)	
· ADR	
A .	
<b>*</b>	
<b>V</b>	
· Class	2 5F Gases.
· Label 	2.1
· IMDG	
<b>*</b>	
· Class	2.1
· Label	2.1
·IATA	
^	
<b>*</b>	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler):	Warning: Gases.
· EMS Number:	F-D,S-U
· 14.7 Transport in bulk according to Ann	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	11
· ADR · Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
Eucepieu quantues (Eg)	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY
	HAZARDOUS

*Printing date 02.06.2015 Version number 53 Revision: 02.06.2015* 

Trade name: MOTIP CAR CARE TYRE SHINE

(Contd. of page 8)

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered.