

USB-C to USB-C angled Connection Cable, 1m

USB 3.2 | 5Gbps | 60W

EN • USB-C 3.2 Gen1 (USB 3.0) for a data transfer speed up to 5Gbps • USB-C male to USB-C angled male connector • Max. power throughput: 20V @ 3A = 60W

NL • USB-C naar USB-C aansluitkabel haaks, 1m **FR** • Câble de connexion coudé USB-C vers USB-C, 1m **IT** • Cavo di collegamento angolato da USB-C a USB-C, 1m **DE** • USB-C auf USB-C abgewinkeltes Verbindungskabel, 1m **ES** • Cable de conexión de USB-C a USB-C en ángulo, 1m **PT** • Cabo de ligação em ângulo USB-C para USB-C, 1m **HU** • USB-C-ről USB-C-re hajlított csatlakozókábel, 1m **CZ** • Úhlový propojovací kabel USB-C na USB-C, 1m **DK** • USB-C til USB-C vinklet tilslutningskabel, 1m **NO** • USB-C til USB-C vinklet tilkoblingskabel, 1m **SE** • Anslutningskabel för USB-C till USB-C med vinklad anslutning, 1m **FI** • USB-C:n ja USB-C:n kulmaYTEyskaapeli, 1m **SI** • Kotni priključni kabel USB-C na USB-C, 1m **BG** • Свързващ кабел USB-C към USB-C под ъгъл, 1m **GR** • Καλώδιο σύνδεσης USB-C σε γωνιακό καλώδιο USB-C, 1m **PL** • Kabel połączeniowy kątowny USB-C do USB-C, 1m

TECHNICAL SPECIFICATIONS

Connector A: USB-C Male

Connector B: USB-C Male angled

Material: Tinned Copper

AWG: #34/32/30/26

Shielding: Braided

Speed: 5Gbps

Max. throughput: 20.0V @ 3.0A=60W

Article: AC7406



8 716065 501902

IIC Code:

Manufactured in China. Please check the website www.act-connectivity.com for the Declaration of Conformity. You can find safety information at www.act-connectivity.com/safety

