

Microwave sensor

- **DE** Tageslicht Sensor ≤ 2 lux / 10 lux / 25 lux / 50 lux
- (bei Deckenaufbau)
 Erfassungsbereich bis 10m (Wandleuchte)
- 6m (Deckenleuchte)
 Einschaltzeiten: 5s-30min
- **GB** Daylight sensor ≤ 2 lux / 10 lux / 25 lux / 50 lux
- (with ceiling mounting)Detection zone up to 10m (wall light) 6m (ceiling light)
- Switch-on times: 5s-30min FR • Capteur de lumière du jour ≤ 2 lux/10 lux/25 lux/50 lux
 - (si fixation au plafond) • Distance de détection jusqu'à 10m (Applique murale) 6m (Plafonnier)
- Temps d'enclenchement : 5s-30min
- IT Sensore crepuscolare ≤ 2 lux/10 lux/25 lux/50 lux (se il fissaggio a soffitto)
 - Campo di rilevamento 10m (Lampada da parete) 6m (Plafoniera)
- Tempo di accensione: 5s-30min

Briloner Leuchten GmbH & Co. KG Am Steinbach 14 · D-59872 Meschede

- ES Sensore crepuscolare ≤ 2 lux/10 lux/25 lux/50 lux (si fijación al techo)
- Rango de detección 10m (Luz de pared) 6m (Plafón)
 Tiempo de conexión: 5s-30min

Sensor: ON/OFF option

- **DE** Override Funktion = Dauerlicht durch Deaktivierung des Sensors per Wandschalter
- **GB** Override function = continuous light by deactivating the sensor via wall switch
- **FR** Fonction de neutralisation = lumière continue en désactivant le capteur via l'interrupteur mural
- IT Funzione di override = luce continua disattivando il sensore tramite interruttore a parete
- ES Función de anulación = luz continua desactivando el sensor mediante un interruptor de pared





Weiß White Blanc Bianco Blanco
















| Art.-Nr. 7187-016

320x330x75mm

BRILO®

LED

| LED 12 W 1300 lm





BRILO® **BRILO**®





LED

| LED 12 W 1300 lm

Neutral white Sensor: Sensor: ON/OFF option



BRILO

LED

1300 lm







www.briloner.com