

SKU: S5PRW-P740



Riff Wireless 2 : True Black  
MODEL : S5PRW  
FCC ID : Y22-S5PRW  
IC : 10486A-S5PRW

EN Safety information inside.  
FR Renseignements sur la sécurité à l'intérieur.  
ES Información sobre seguridad en el interior.  
DE Sicherheitshinweise innen.  
ZH 安全信息在内  
JP 安全情報を内部に含む。

Americas  
Skullcandy, Inc.  
6301 N Landmark Dr.  
Park City, UT 84098  
U.S.A.  
Skullcandy.com

Europe  
Skullcandy Europe BV  
Postbus 425  
5500AK Veldhoven  
Nederland  
Skullcandy.eu

Canada  
Skullcandy Canada ULC  
329 Railway St. Unit 205  
Vancouver, BC. V6A 1A4  
Canada  
Skullcandy.ca

Skullcandy UK LTD  
Andrews House  
College Road  
Guildford  
GU1 4QB  
Skullcandy.co.uk

EN Made in Philipines.  
FR Fabriqué aux Philippines.  
ES Hecho en Filipinas.  
ZH 菲律宾制造

EN contains Li-ion battery. Battery must be recycled or disposed of properly.  
FR contient batterie Li-ion. Batterie doit être recyclée ou jetées correctement.  
ES contiene una batería Li-ion. La batería debe ser reciclada o desechada adecuadamente.

© 2021 Skullcandy, Inc.  
Skullcandy.com/patent-information

NEW MATERIAL ONLY  
REG. NO. 09T-01675114  
POLYURETHANE FOAM

MATÉRIAUX NEUFS SEULEMENT  
N° DE PERMIS 09T-01675114  
MOUSSE DE POLYURETHANE

Contents

- Wireless Headphones
- USB-C Charging Cable
- Backup Aux Cable
- User Guide
- Warranty information at: skullcandy.com/warranty

Contenu

- Écouteurs Sans Fil
- Câble de Recharge USB-C
- Câble Auxiliaire de Secours
- Guide de l'Utilisateur
- Renseignements sur la garantie à: skullcandy.com/warranty

Contenido

- Auriculares Inalámbricos
- Cable de Carga USB-C
- Cable Auxiliar de Respaldo
- Manual de Instrucciones
- Información sobre la garantía en: skullcandy.com/warranty

EN Speaker Driver: 40mm, Impedance: 32 Ohms, THD <1% @ 1KHz, Voltage Regulation: 3.7v, Bluetooth® 5.2 Single Mode, Frequency Band: 2402 MHz – 2480 MHz, Maximum Power: 11.6dBm, Weight: 160g. FR Driver Président: 40mm, Impédance: 32 Ohms, THD <1% à 1KHz, Tension: 3.7v, Bluetooth® 5.2 Mode Simple, Bande de fréquence: 2402MHz – 2480MHz, Puissance Maximum: 11.6dBm, Poids: 160g. ES Controlador del altavoz: 40mm, Impedancia: 32 Ohms, THD <1% a 1KHz, Voltaje: 3.7v, Modo Simple Bluetooth® 5.2, Banda de frecuencia: 2402MHz – 2480MHz, Poder Maximo: 11.6dBm, Peso: 160g. DE Lautsprecher -Treiber: 40mm, Impedanz: 32 Ohm, THD <1% bei 1KHz, Spannungsregelung: 3,7 V, Bluetooth® 4.1 Einzelmodus Frequenzband: 2402MHz – 2480MHz, Maximale Performance: 11.6dBm, Gewicht: 160g. JP スピーカードライバー: 40ミリメートル, インピーダンス: 32オーム, THD<1%@ 1KHzの, 電圧レギュレーション: 3.7Vの, のBluetooth®5.2 シングルモード, 周波数帯: 2402MHz – 2480MHz, 最大パフォーマンス: 11.6dBm, 重量: 160グラム。ZH 扬声器驱动器: 40毫米, 阻抗: 32欧姆, THD <1%@1KHz, 电压调节: 3.7V, 蓝牙5.2单一模式, 频带: 2402MHz – 2480MHz, 最大功率: 11.6dBm, 重量: 160克。

EN Skullcandy, and other marks are registered trademarks of Skullcandy, Inc. All rights reserved.  
FR Skullcandy, et les autres marques sont des marques déposées de Skullcandy, Inc. Tous droits réservés.  
ES Skullcandy, y las demás marcas son marcas registradas de Skullcandy, Inc. Todos los derechos reservados.

EN The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Skullcandy, Inc. is under license. FR La marque verbale et les marques figuratives Bluetooth® sont des marques déposée de la société Bluetooth SIG, Inc. et toute utilisation de ces marques par Skullcandy, Inc. s'effectue sous licence.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



018-210461



R-C-Sku-S5PRW



UK CA



PPB



EAC NOM

