

# GLS BULB E27 1055LM 9.5W 5000K NON-DIMM 240 BEAM FROSTED INTEGRAL

ILGLSE27NF114



This 9.5W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a cool white light and brightness, similar to a 75W filament bulb. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for living rooms, hallways and kitchens

#### **Details**

Quick Order Code: 011981

**Barcode**: 5055788258957

Category:LampsRange Name:Everyday

Market Segment: Commercial indoor, Residential indoor

Finish: Frosted

Warranty (Years): 2
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 60
Product Width (mm): 60
Product Weight (g): 36

Material: Plastic and Aluminium heat-sink, Injection moulded

diffuser

Base Term: Edison screw

Bulb Base:E27Construction:PlasticGlobe Finish:FrostedGlobe Type:GLSBulb or Luminaire Shape:Round

Placement / Application: Indoor, General Lighting

Spot Type: SMD

#### **Electrical Data**

Power Consumption (w): 9.5
Power Factor: 0.5
Wattage equivalent (W): 75

Amperage (mA): 72

**Dimming:** Non-Dimmable

Driver Included:YesElectric Current:ACTrue Wattage Eq (W):75

**EN:** EN-62560

LVD Certified: Yes

## **Light Data**

Luminous Flux in Lumens (Im): 1055 Luminous efficacy (Im/W): 111 Correlated Colour Temperature (CCT) (K): 5000

**Colour Temperature:** 5000K - Daylight

Colour Temperature Name:DaylightBeam Angle:240Colour Rendering Index (CRI):80Colour Type:SingleFrequency Range (Hz):50/60Instant on (Less than 1 second):Yes


**LED Type:** Surface mounted device (SMD)


Lifetime (hours): 15000
Switching Cycles: 30000
Useful Lumens (Im): 1055

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating: A**+ E **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





# **Packaging**

Package Weight (g):	61
Package Length (mm):	120
Package Width (mm):	65
Package Depth (mm):	65