

Product information | TECHNICAL DATA SHEET

MTN 94. Solid Colors. Matt paint, low pressure, high coverage and fast drying times.
400 ml, 11 Oz, 312 g.

GENERAL DESCRIPTION

This is a spray paint with a matt finish. It is made with next generation modified alkyd resins and has been developed to meet the highest demands from the graffiti and fine arts market, and is also adaptable to the needs of interior and exterior decoration. Designed and formulated with the highest quality products, with the focus always being on color consistency, fast drying, and without forgetting respect for the user and the environment. Its name is in honor of the year in which the company was founded.

FEATURES

- Low pressure.
- Fast drying.
- Good hardening.
- Excellent flexibility.
- Strong resistance to scratching once the film is polymerized.
- Does not contain lead nor other heavy metals.
- Good covering capability.
- Color durability.
- Easy to apply and repaint.
- Very good resistance to the sun and rain.
- Very good resistance to UV light (see chart).

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush and prepare an anti-rust primer if considered necessary. Apply an anchor layer on plastics and polyesters.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use.
If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Low pressure:	Polyvalent female valve
Propellant:	Butane / Propane / Mix
Type of liant:	Modified alkyd
Color:	See chart
Shine 60° (ASTM D-523 ISO 2813):	15-25% matt
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	24 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15 micras/layer
Adherence (ASTM D-3359 ISO 2409):	0 B
Theoretical yield (continuous painting):	3 m² for 400 ml
Thinner:	Ethyl acetate
Product life:	(Well Stored) 10 Years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity 85% R.H.P
Heat resistance of paint:	100°C

* All of the adherence tests have been carried out on iron plates.

APPLICATIONS

Due to the product's features we recommend its use in precision jobs and given its matt finish and thus its anti-reflective qualities, we would especially recommend it for photographic and artistic jobs. May also be used in:

- DIY
- Gardening
- Transport
- Fine arts
- Graffiti
- Sign painting
- Plumbing
- Industry
- Muralism

APPEARANCE



LABEL



CAP SYSTEM



CAUTION



COLORS 216 Colors

RV 189	RV 192	RV 190	RV 191	RV 193	RV 194	RV 196	RV 197	RV 321	RV 310
RV 20	RV 102	RV 1013	RV 94	RV 115	RV 164	RV 86	RV 176	RV 195	RV 311
RV 109	RV 103	RV 135	RV 95	RV 3017	RV 165	RV 87	RV 203	RV 322	RV 171
RV 1021	RV 50	RV 136	RV 96	RV 116	RV 4003	RV 88	RV 204	RV 170	RV 172
RV 110	RV 105	RV 137	RV 97	RV 3001	RV 4010	RV 89	RV 205	RV 323	RV 173
RV 111	RV 106	RV 138	RV 98	RV 47	RV 166	RV 90	RV 200	RV 276	RV 174
RV 112	RV 2004	RV 139	RV 100	RV 3004	RV 167	RV 91	RV 64	RV 275	RV 175
RV 113	RV 107	RV 140	RV 35	RV 3007	RV 168	RV 92	RV 201	RV 283	RV 28
RV 114	RV 108	RV 141	RV 101	RV 77	RV 169	RV 93	RV 202	RV 274	RV 27
RV 312	RV 184	RV 185	RV 186	RV 187	RV 188	RV 270	RV 267	RV 1017	RV 278
RV 313	RV 149	RV 156	RV 142	RV 124	RV 1016	RV 269	RV 266	RV 1028	RV 277
RV 314	RV 150	RV 157	RV 6027	RV 16	RV 129	RV 268	RV 265	RV 207	RV 279
RV 315	RV 151	RV 158	RV 144	RV 34	RV 60	RV 199	RV 281	RV 177	RV 3020
RV 316	RV 152	RV 159	RV 145	RV 125	RV 130	RV 182	RV 282	RV 178	RV 241
RV 317	RV 30	RV 160	RV 5018	RV 6018	RV 131	RV 183	RV 272	RV 8023	RV 245
RV 318	RV 5005	RV 161	RV 146	RV 126	RV 132	RV 179	RV 273	RV 99	RV 243
RV 319	RV 154	RV 162	RV 147	RV 127	RV 133	RV 180	RV 271		
RV 320	RV 5013	RV 163	RV 148	RV 6009	RV 134	RV 181	RV 280		
				FLUORESCENTS		SPECTRALS			
RV 198	RV 300	RV 305	R 9010	Amarillo Fluorescente Fluorescent Yellow	Amarillo Étereo Ethereal Yellow	Blanco Aire Air White	Gris Sombra Shadow Grey	Negro Sombra Shadow Black	
RV 7047	RV 301	RV 306	R 9011	Naranja Fluorescente Fluorescent Orange	Naranja Calima Calima Orange				
RV 118	RV 302	RV 307	Plata Joya Jewel Silver	Rojo Fluorescente Fluorescent Red	Rojo Alma Soul Red				
RV 7040	RV 303	RV 308	Oro Marco Frame Gold	Fucsia Fluorescente Fluorescent Fuchsia	Marrón Judía Judía Brown				
RV 119	RV 304	RV 309		Violeta Fluorescente Fluorescent Violet	Verde Brisa Breeze Green				
RV 120				Verde Fluorescente Fluorescent Green	Azul Atmosfera Atmosphere Blue				
RV 121				Azul Fluorescente Fluorescent Blue	Violeta Aura Aura Violet				
RV 7016									
RV 78									

Due to technical reasons this color chart might not reproduce the real colors. For accurate color reference see the spraycan's Donut. © Montana Colors 2019.



PACKAGING

Low pressure.
 Nominal capacity 400ml.
 Heat resistance of packaging: <50°C
 Propellant: GLP – HC C₃-C₄

Box (6 units)
 205 X 140 X 200 mm.



DISPLAY RACK

Height / Width / Depth
 205 x 98,50 x 50 cm
 Capacity: 546 sprays.
 References: 91
 SPAT2405007

