# **EU-TYPE EXAMINATION CERTIFICATE**



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

**Certificate N°** 0075/4541/161/03/22/0503

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment : **Gerba Shoes BV** Manufacturer : Solingenstraat 43, 7421 ZR Deventer

**Netherlands** 

Description

**PPE Type :** 

**Product reference :** 

Article code :

Construction and material of outsole : Pictures :

a safety footwear Springfield

Injection, PU/PU



Springfield EN ISO 20345:2011 S1P SRC SIZE: EUR 42

09/2021 Solingenstraat 43, 7421 ZR Deventer, Netherlands

#### **Reference standard :** EN ISO 20345 : 2011

**Classification : I** 

Size range : 36-48

Category : S1P SRC

### **Toecap nature : Non Metallic**

Slip resistance : SRC

### **Insert nature : Non Metallic**

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the instruction for use index N°V1-2021 and in the manufacturer's technical file index 01 dated from MARCH 2022

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate

Nadine PIPAZ

CE Expert Team Coordinator



Date of first issue: 15 March 2022 End of validity date : 15 March 2027



#### cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France

MARKIN TIFIED BOD VCT





In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroguinerie Ganterie Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

Issued in Lyon by

Gerba Shoes BV

# **MANUFACTURER'S TECHNICAL FILE**

Reference of the product :	Springfield
Article code :	/
Technical file index :	01
Last update :	MARCH 2022

# **IDENTIFICATION**

Reference of the product :	Springfield
Article Code :	/
Basic model	
Technical file index :	01
Last update :	MARCH 2022

### Manufacturer :

Gerba Shoes BV Solingenstraat 43, 7421 ZR Deventer Netherlands tel : 0570 510153 fax : N/A

#### Factory :

Ruian Pengda Shoes Co.,Ltd

No.371, Kaifa yi Road, Economic Development Zone, Ruian City, Zhejiang, 325200

China Tel : 137 0578 2718 Fax : n.a

## FOOTWEAR DESCRIPTION

#### Footwear description:

The classification of this footwear is: I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear

The design of this footwear is: A : low shoe

#### **Visual description:**

General view :



Outsole view :



Reference of the mould : ST-36

#### Range of sizes :

36-48

#### Construction and material of outsole :

Injection, PU/PU

#### Field of use

Construction, automobile industry, Wearhouse for mechanical risks

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
	Deminente defined in the Anney US4 are applicable to		Standard
<b>§1</b>	Requirements defined in the Annex II §1 are applicable to all PPE	$\checkmark$	✓ Instruction for use
	ан РРЕ		✓ Marking
	Manufacturer's instructions and information is available	7	Standard
§1.4			✓ Instruction for use
			Marking
	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	~	Standard
§2.2			✓ Instruction for use
			Marking
	If it is known that the design performance of new PPE	2	Standard
§2.4	may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and		✓ Instruction for use
	unambiguously marked on each item of PPE placed on the market and on its packaging.		Marking
			Standard
§2.6	PPE is intended for use in potentially explosive atmospheres	7	✓ Instruction for use
			✓ Marking
§2.9	DDF incompositing components which can be editected as	7	Standard
	PPE incorporating components which can be adjusted or removed by the user		✓ Instruction for use
			Marking
PPE	PPE bearing one or more identification markings or	7	Standard
§2.12	indicators directly or indirectly relating to health and safety		✓ Instruction for use
			Marking
	Multi-risk PPE	~	Standard
§2.14			✓ Instruction for use
			✓ Marking
	The PPE is intended to protect against impact caused by		Standard
§3.1.1	falling or ejected objects and collisions of parts of the body with an obstacle	1	✓ Instruction for use
			✓ Marking
	The PPE is intended to protect against falls due to	~	Standard
§3.1.2.1	slipping		✓ Instruction for use
			✓ Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	7	Standard
			Instruction for use
			✓ Marking
	The PPE is intended to protect against mechanical injuries	7	Standard
§3.3			✓ Instruction for use
			✓ Marking

# FOOTWEAR CONSTITUTION

	Ref	Material	Color
UPPER	VL-U7	COW SPLIT NUBUCK LEATHER (with grey printing)	BLACK/GREY
COLLAR	VL-U7	COW SPLIT NUBUCK LEATHER	Black
TONGUE	VL-U3	pu	Black
	VL-U7	COW SPLIT NUBUCK LEATHER	Black
VAMP LINING	L-1	SANDWICH MESH	Grey
QUARTER LINING	L-1	SANDWICH MESH	Grey
INSOCK	ISC-2	VELOURS+EVA WITH PERFORATED//removable & perforated	BLACK/GREY
OUTSOLE	ST36	PU/PU	BLACK/Grey
INSOLE	DYNA-FLEX	composite penetration insole	White/Orange
TOE CAP	802	composite toecap	Beige
INSERT	DYNA-FLEX	composite penetration insole	White/Orange
DECORATIVE ELEMENTS	$\langle (((((((((((((((((((((((((((((((((((($	PVC	Black
		metal eyelets	Black
	$\mathcal{M}$	Stripe	Black

### **PROTECTION SCOPE**

#### **Basic requirements :**

This product has been designed to be a safety footwear.

The technical rules are :

European Standard EN ISO 20344 : 2011 Personal protective equipment - test methods for footwear European Standard EN ISO 20345 : 2011 : Personal protective equipement - Safety footwear

It is a category II product

Requirement of the standard EN ISO 20345 : 2011 concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution and steel floor with glycerol (SRC)

Requirement of the paragraph 5.8.1. Design of the standard EN ISO 20345 : 2011 concerning cleated outsole.

At the date of certificate, the product is in compliance with Annex XVII of European REACh regulation (n° 1907/2006 and revisions)

#### Additional requirements :

The additional requirements are :

- Closed seat region
- Antistatic footwear
- Energy absorption of seat region
- Fuel oil resistance
- Penetration resistance

# MARKING - PACKAGING

#### Information printed on the footwear :

- \* Logo of the Manufacturer
- \* Logo CE
- \* Manufacturer's type designation
- \* Postal address of manufacturer
- \* Footwear's reference
- \* Article code
- \* Size
- \* Year of manufacture and at least quarter
- \* The number and year of the Standard used
- \* The symbol(s) of the additional requirements

#### Marking example :



Springfield

/

Springfield EN ISO 20345:2011 S1P SRC SIZE: EUR 42 09/2021

The location of marking is : tongue inside

Solingenstraat 43, 7421 ZR Deventer, Netherlands

#### Method of marking on the footwear :

STITCHING

Packaging :

1 pair in a box,10 boxes in a carton

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	References
СТС	D170915831_1
CTC	D200201710_1
CTC	D201016083_1
CTC	D210611937_1
CTC	D210712937_1
CTC	D210815010_1
CTC	D210815849_1
CTC	D211019468_1
CTC	D211122051_1
CTC	D211123527_1
CTC	D211226492_1
INTERTEK	GZHT90950501(S1)
INTERTEK	GZHT90971255

# **MEANS OF CONTROL**

There are 5 main steps for quality control in our factory.the details are as follows:

1, Material quality control.When new material is sent to our factory,our QC will inspect carefully,the bad quality material will return back to supplier and the good material will store in our warehouse. and we use The standard EN ISO 20345:2011 standard to control all raw material accordingly.

2, Procedure control. We have several QC for every proceduce, such as, cutting, stiching, shaping, injecting, if there is problem in the making procedudes, the bad uppers or outsoles will pick out by QC, then destory them together, this is to make sure there is no bad quality components for next step.

3, Final inspection. After the shoes finish, our QC will inspect the shoes by random, if the bad shoes fill in more than 2%, all shoes will be inspected again, then pick up the bad shoes and remake them.

4, Bad quality reaction and quality improvement.All production department should analyse the situation for quality and give suggestion on how to improve the quality.Then to make sure our shoes quality become better and better.

5, pertinent tests: impact resistance, compression resistance, penetration force, antistatic resistance under EN ISO 20345:2011; frequency: batch test.

### PPE subject to ageing :

Peremption period : 2 years when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

### **Declaration of conformity :**

Available with product.