

## Assembly Manual:



- 1** Content: 1 Trailer frame/ bag, 1 front wheel, 2 rear wheels, 1 flag, 1 towing arm (including 2 clevis pins), 1 rain cover.



- 2** Push rear wheel to the bottom of axle till the spring clip clicks. Check both wheels are securely locked by pulling.



- 3** Insert the front wheel axle into the slot till hearing the spring clip click. Check the front wheel is securely locked by pulling. (Skip this step if you are going to use it as a bicycle trailer)



- 4** Unfold the trailer by pulling backwards the trailer frame as shown in the photo.



- 5** Press both sides' supporting arm till the end and make sure each side of the supporting arm is properly locked.



- 6** a. Securely install the towing arm on the rear wheel axle as the picture shown.



- b. Insert the towing arm through both clevis. Secure towing arm by inserting the clevis pin through clevis and towing arm. Properly secure clevis pin by setting the safety wire over the tip of clevis pin.



- c. Insert the bar into the slot of connecting plate. Secure the bar by inserting bolt and set the bolt ring over the end of bar.



- 7** Slide the flag pole into the left pocket as shown in the photo.

**InnoPet**

## Sporty Dog Trailer

### Folding steps:



- 1** Release the lock.



- 2** Press down the spring clip to remove each wheel.



- 3** During the stroller state, secure towing bar inside stroller by Velcro straps as shown in the photo. Remember to take out the towing bar before flatten stroller.

### Rain cover:



- 1** place the hook around the front wheel axle to secure rain cover.

