

**G4 BULB 100LM 1.1W 2700K NON-DIMM 260 BEAM CLEAR INTEGRAL**

ILG4NC003



Integral LED G4 lamps run at less than 2W and offer a lifetime of thousands of hours more than their halogen equivalents. This makes them an ideal retrofit for existing G4 fittings.

**Details**

<b>Quick Order Code:</b>	592196
<b>Barcode:</b>	5055788224501
<b>Category:</b>	Lamps
<b>Range Name:</b>	G4
<b>Product Type:</b>	G4
<b>Market Segment:</b>	Commercial indoor, Residential indoor
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	30
<b>Product Width (mm):</b>	9.5
<b>Product Weight (g):</b>	2
<b>Material:</b>	Silicone
<b>Base Term:</b>	G4
<b>Bulb Base:</b>	G4
<b>Construction:</b>	Silicone
<b>Globe Finish:</b>	Clear
<b>Bulb Fixing:</b>	Pendant, Wall, Desktop
<b>Bulb or Luminaire Shape:</b>	Oval
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power (W):</b>	1.1
<b>Power Consumption (w):</b>	1.1
<b>Power Factor:</b>	0.7
<b>Wattage equivalent (W):</b>	10
<b>Amperage (mA):</b>	90
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	No, needs 12V AC/DC Transformer

**Electric Current:** AC/DC  
**EN:** EN 61547:2009

## Light Data

**Luminous Flux in Lumens (lm):** 100  
**Luminous efficacy (lm/W):** 91  
**Correlated Colour Temperature (CCT) (K):** 2700  
**Colour Temperature:** 2700K - Warm  
**Colour Temperature Name:** Warm  
**Beam Angle:** 260  
**Colour Rendering Index (CRI):** 80  
**Instant on (Less than 1 second):** Yes  
**LED Type:** COB  
**Lifetime (hours):** 15000  
**Switching Cycles:** 7500

## Environment

**EN:** EN 61547:2009  
**CE RoHS:** Yes  
**Energy Rating:** A++  
**New Energy Rating:** F  
**Hg 0% (Mercury Free):** Yes  
**IP Rating (Ingress Protection):** IP20  
**Lowest Operating Temperature (°C):** -20  
**Maximum Operating Temperature (°C):** 40



## Packaging

**Package Weight (g):** 2.3  
**Package Length (mm):** 37  
**Package Width (mm):** 15  
**Package Depth (mm):** 15

[Portal.integral-led.com](http://Portal.integral-led.com)