

**LUXE BASS**

# DESK CHARGER

5-PORTS USB QC3.0 & PD

**75W**



EN

Specifications

Type: Desktop Charger

Input: 100-240V 50/60Hz 1.5A

Output:

USB-C (PD-45W) : 5V=3A / 9V=3A / 12V=3A / 15V=3A

USB-C (Type-C) : 5V=2A

USB: 5V=2.4A

USB: 5V=2.4A

USB (QC3.0) : 3.6V-6.5V=3A / 6.5V-9V=2A / 9V-12V=1.5A

USB Port: 2 USB Type-C + 2 USB + 1 QC 3.0 (USB)

Working temperature: -10°C-50°C



DE

Spezifikationen

Typ: Desktop-Ladegerät

Input: 100-240V 50/60Hz 1.5A

Output:

USB-C (PD-45W) : 5V=3A / 9V=3A / 12V=3A / 15V=3A

USB-C (Type-C) : 5V=2A

USB: 5V=2.4A

USB: 5V=2.4A

USB (QC3.0) : 3.6V-6.5V=3A / 6.5V-9V=2A / 9V-12V=1.5A

USB-Eingang: 2 USB Type-C + 2 USB + 1 QC 3.0 (USB)

Arbeitstemperatur: -10°C-50°C



FR

Spécifications

Type: Chargeur de bureau

Entrée: 100-240V 50/60Hz 1.5A

Sortie:

USB-C (PD-45W) : 5V=3A / 9V=3A / 12V=3A / 15V=3A

USB-C (Type-C) : 5V=2A

USB: 5V=2.4A

USB: 5V=2.4A

USB (QC3.0) : 3.6V-6.5V=3A / 6.5V-9V=2A / 9V-12V=1.5A

Entrée USB: 2 USB Type-C + 2 USB + 1 QC 3.0 (USB)

Température de fonctionnement: -10°C-50°C



NL

Specificaties

Type: Bureauoplader

Input: 100-240V 50/60Hz 1.5A

Output:

USB-C (PD-45W) : 5V=3A / 9V=3A / 12V=3A / 15V=3A

USB-C (Type-C) : 5V=2A

USB: 5V=2.4A

USB: 5V=2.4A

USB (QC3.0) : 3.6V-6.5V=3A / 6.5V-9V=2A / 9V-12V=1.5A

USB Ingang: 2 USB Type-C + 2 USB + 1 QC 3.0 (USB)

Functioneringstemperatuur: -10°C-50°C



view website

Designed in Germany  
Manufactured in China  
Innsbruckweg 202, Rotterdam  
The Netherlands  
www.all4gadgets.nl



8 720624 381348

MADE IN CHINA MODEL: PD-75W

5-PORTS DESK CHARGER STATION 75W