




Meaningful Innovation.

WEEE Number: 80133970

## INSTRUCTION MANUAL SOLAR FOLDING PANEL

### TECHNICAL DATA:

|  |  |
|--|--|
| MODEL  | VT-10241   |
| SKU  | 11565  |
| Solar Panel Watts  | 120W(-5%,+10%)   |
| Folding method   | 1*4 fold   |
| Folded size  | 430*540*54±5mm; Folding thickness: 25 (with junction box) mm±5mm |
| Expanded size  | 1930*430*25±5mm; Folded thickness: 25 (with junction box) mm±5mm |
| Weight of a single product   | 12.8Kg±0.5Kg   |
| Operation Temperature  | -20C to 60C  |
| Surface material: ETFE (a fluorine-containing plastic film, which is specially designed for anti-UV (ultraviolet), not easy to age, has a long service life, and has the characteristics of good dustproof ability.) |  |



**IP67**  
RATING

**02**  
YEAR  
WARRANTY\*

### INTRODUCTION & WARRANTY

Thank you for selecting and buying V-TAC product. V-TAC will serve you the best. Please read these instructions carefully before starting the installation and keep this manual handy for future reference. If you have any other query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best. The warranty is valid for 2 years from the date of purchase. The warranty does not apply to damage caused by incorrect installation or abnormal wear and tear. The company gives no warranty against damage to any surface due to incorrect removal and installation of the product. This product is warranted for manufacturing defects only.

### WARNING!

1. Please make sure to turn off the power before starting the installation.
2. Installation must be performed by a qualified electrician.
3. If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.
4. This product cannot be in contact with strong corrosive substances.
5. Avoid hitting and scratching the surface with hard objects during use.
6. Cannot withstand bending stress during transportation and assembly.




This marking indicates that this product should not be disposed of with other household wastes.



**MULTI-LANGUAGE  
MANUAL QR CODE**

Please scan the QR code to access the manual in multiple languages.




Caution, risk of electric shock.

### PACKAGING

|                 |             |             |
|-----------------|-------------|-------------|
| PROTECTIVE CASE | SOLAR PANEL | USER MANUAL |
|                 |             |             |

### INSTALLATION




Unfold the solar panel

Open the kickstands

Face the sun

Connect the charging cable

### CHARGING FOR POWER STATION



### ELECTRICAL PERFORMANCE PARAMETERS OF STANDARD LIGHT INTENSITY

| No | Performance                  | Standard Parameter | Minimum parameter |
|----|------------------------------|--------------------|-------------------|
| 1  | MC4 Output power (W)         | 112                | ≥106.4            |
| 2  | MC4 Output voltage (V)       | 17.6               | ≥16.72            |
| 3  | MC4 Output current (A)       | 6.36               | ≥4.71             |
| 4  | MC4 Open circuit voltage (V) | 21.2               | ≥22.8             |
| 5  | MC4 Short circuit current(A) | 6.83               | ≥4.97             |

Cell: Monocrystalline silicon cell (182\*182mm, conversion efficiency of cell is 22.6%)



IN CASE OF ANY QUERY/ISSUE WITH THE PRODUCT, PLEASE REACH OUT TO US AT: SUPPORT@V-TAC.EU  
FOR MORE PRODUCTS RANGE, INQUIRY PLEASE CONTACT OUR DISTRIBUTOR OR NEAREST DEALERS.  
V-TAC EUROPE LTD. BULGARIA, PLOVDIV 4000, BUL.L.KARAVELOW 9B