

TP-LINK®

User Guide

NC220

Day/Night Cloud Camera, 300Mbps Wi-Fi

NC230

HD Day/Night Wi-Fi Cloud Camera

NC250

HD Day/Night Cloud Camera, 300Mbps Wi-Fi



COPYRIGHT & TRADEMARKS

Specifications are subject to change without notice. **TP-LINK®** is a registered trademark of TP-LINK TECHNOLOGIES CO., LTD. Other brands and product names are trademarks or registered trademarks of their respective holders.

No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK TECHNOLOGIES CO., LTD. Copyright © 2017 TP-LINK TECHNOLOGIES CO., LTD. All rights reserved.

<http://www.tp-link.com>

FCC STATEMENT



This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/ TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1) This device may not cause harmful interference.
- 2) This device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modifications could void the user's authority to operate the equipment.

FCC RF Radiation Exposure Statement:

This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This device and its antenna must not be co-located or operating in conjunction with any other antenna or transmitter.

"To comply with FCC RF exposure compliance requirements, this grant is applicable to only Mobile Configurations. The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter."

CE Mark Warning



This is a class B product. In a domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.

RF Exposure Information

This device meets the EU requirements (1999/5/EC Article 3.1a) on the limitation of exposure of the general public to electromagnetic fields by way of health protection.

The device complies with RF specifications when the device used at 20 cm from your body.

Canadian Compliance Statement

This device complies with Industry Canada license-exempt RSSs. Operation is subject to the following two conditions:

- 1) This device may not cause interference, and
- 2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

- 1) l'appareil ne doit pas produire de brouillage;
- 2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Radiation Exposure Statement:

This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Déclaration d'exposition aux radiations:

Cet équipement est conforme aux limites d'exposition aux rayonnements IC établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec un minimum de 20 cm de distance entre la source de rayonnement et votre corps.

Industry Canada Statement

CAN ICES-3 (B)/NMB-3(B)

Korea Warning Statements:

당해 무선설비는 운용중 전파혼신 가능성이 있음.

NCC Notice

注意！

依據 低功率電波輻射性電機管理辦法

第十二條 經型式認證合格之低功率射頻電機，非經許可，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性或功能。

第十四條 低功率射頻電機之使用不得影響飛航安全及干擾合法通行；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。前項合法通信，指依電信規定作業之無線電信。低功率射頻電機需忍受合法通信或工業、科學以及醫療用電波輻射性電機設備之干擾。

減少電磁波影響，請妥適使用。

BSMI Notice

安全諮詢及注意事項

- 請使用原裝電源供應器或只能按照本產品注明的電源類型使用本產品。
- 清潔本產品之前請先拔掉電源線。請勿使用液體、噴霧清潔劑或濕布進行清潔。
- 注意防潮，請勿將水或其他液體潑灑到本產品上。
- 插槽與開口供通風使用，以確保本產品的操作可靠並防止過熱，請勿堵塞或覆蓋開口。
- 請勿將本產品置放於靠近熱源的地方。除非有正常的通風，否則不可放在密閉位置中。
- 請不要私自打開機殼，不要嘗試自行維修本產品，請由授權的專業人士進行此項工作。



Продукт сертифіковано згідно с правилами системи УкрСЕПРО на відповідність вимогам нормативних документів та вимогам, що передбачені чинними законодавчими актами України.





Safety Information

- When product has power button, the power button is one of the way to shut off the product; when there is no power button, the only way to completely shut off power is to disconnect the product or the power adapter from the power source.
- Don't disassemble the product, or make repairs yourself. You run the risk of electric shock and voiding the limited warranty. If you need service, please contact us.
- Avoid water and wet locations.
- Adapter shall be installed near the equipment and shall be easily accessible.
- The plug considered as disconnect device of adapter.



- Use only power supplies which are provided by manufacturer and in the original packing of this product. If you have any questions, please don't hesitate to contact us.

Explanation of the symbols on the product label

Symbol	Explanation
	DC voltage
	<p>RECYCLING</p> <p>This product bears the selective sorting symbol for Waste electrical and electronic equipment (WEEE). This means that this product must be handled pursuant to European directive 2012/19/EU in order to be recycled or dismantled to minimize its impact on the environment.</p> <p>User has the choice to give his product to a competent recycling organization or to the retailer when he buys a new electrical or electronic equipment.</p>

CONTENTS

Chapter 1 About This Guide	1
1.1 Conventions.....	1
1.2 Overview of This Guide.....	1
Chapter 2 Get to Know Your Camera	3
2.1 Product Overview	3
2.2 Main Features.....	3
2.3 Panel Appearance	4
2.3.1 Front Panel.....	4
2.3.2 Rear Panel	5
Chapter 3 Set Up Your Camera	7
3.1 Set up the Camera with the tpCamera App	7
3.2 Position Your Camera.....	8
Chapter 4 Configure Your Camera	10
4.1 Log in to Your Camera.....	10
4.2 Live View	11
4.3 Basic.....	13
4.3.1 Basic > Status	13
4.3.2 Basic > Network	15
4.3.3 Basic > Wireless Connection	16
4.3.4 Basic > Cloud Setting	18
4.3.5 Basic > LED	19
4.4 Advanced.....	19
4.4.1 Advanced > Status.....	20
4.4.2 Advanced > Network.....	20
4.4.3 Advanced > Wireless Connection.....	22
4.4.4 Advanced > Wireless Extender	24
4.4.5 Advanced > Cloud Setting	25
4.4.6 Advanced > Video.....	25
4.4.7 Advanced > Motion Detection.....	27
4.4.8 Advanced > Sound Detection	28
4.4.9 Advanced > Notification Delivery.....	29
4.4.10 Advanced > LED	33
4.5 System.....	33
4.5.1 Account	34
4.5.2 Date/Time.....	36
4.5.3 Management	38
4.5.4 System Log	39

Chapter 1 About This Guide


This User Guide contains information for setup and management of the Cloud Camera. When using this guide, please notice that features may vary slightly depending on the model and software version you have, and on your location, and language. All images, parameters and descriptions documented in this guide are used for demonstration only.

1.1 Conventions

In this Guide the following conventions are used:

- The camera mentioned in this Guide stands for NC220, NC230 and NC250 without any explanation.
- This User Guide is shared by NC220, NC230 and NC250. NC250 is used for demonstration in this guide. The difference between them are:
 1. Max Frame Rate: 30 fps for NC220 at 640x480 (VGA) and 320x240 (QVGA); 20 fps for NC230 at 1280x720 (HD); NC250 at 1280x720 (HD).
 2. Wi-Fi Data Rate: 150Mbps for NC230; 300Mbps for NC220 and NC250.

Symbol in this Guide:

Symbol	Description
Bold font	Indicates a button, a toolbar icon, menu or menu item.
 Note:	Ignoring this type of note might result in a malfunction or damage to the device.

1.2 Overview of This Guide

Chapter	Introduction
Chapter 1 About This Guide	Introduces the guide structure and conventions.
Chapter 2 Get to Know Your camera	Introduces the features, application and appearance of the camera.
Chapter 3 Set Up Your Camera	Introduces how to quickly set up the camera using the tpCamera app and how to position your camera.

NC220 Day/Night Cloud Camera, 300Mbps Wi-Fi
NC230 HD Day/Night Wi-Fi Cloud Camera
NC250 HD Day/Night Cloud Camera, 300Mbps Wi-Fi

Chapter	Introduction
Chapter 4 Configure Your Camera	Introduces how to configure the camera using the built-in web management page.

Chapter 2 Get to Know Your Camera

2.1 Product Overview

TP-LINK Cloud Camera is a versatile solution for home and office monitoring to keep an eye on your home, kids or workplace, whatever you care for most.

TP-LINK Cloud Camera is a cloud-based Wi-Fi video monitoring device with free live streaming and remote viewing, which makes it easy to stay connected with what you care most wherever you are. You can view and manage your camera from anywhere over the internet through the TP-LINK Cloud website or through the tpCamera app for iOS and Android devices.

Through the camera's web management page, you can view the status of the camera, and configure lots of settings of the camera, such as network setting, the cloud setting, the motion detection, and the notification delivery.

With Night Vision function, TP-LINK Cloud Camera lets you view even in darkness.

With Motion Detection function, TP-LINK Cloud Camera can send you immediate notification by email or FTP whenever motion or sound is detected automatically, allowing you to remain aware of whatever is happening on the ground.

With a stable high speed Wi-Fi connection of up to 300Mbps for NC220 and NC250, and 150Mbps for NC230, you can enjoy fluid video streaming with ease. In addition, the TP-LINK Cloud Camera can also expand your Wi-Fi network with its Wi-Fi Extender functionality.

With the sticky pad or screws, you can place your camera anywhere you want, on the table, the wall, or even on the ceiling.

2.2 Main Features

- Night Vision - Automatic night vision functionality supports 24-hour surveillance
- tpCamera App - Use the free tpCamera app to set up, view and manage the camera remotely with your iOS and Android devices
- Easy Setup – Connect and follow the tpCamera app's instruction to install and operate the camera within minutes
- TP-LINK Cloud (<http://www.tplinkcloud.com>) access for easy viewing and management
- Web management page for basic and advanced configurations
- Motion & Sound Detection - Immediate notification by email or FTP whenever motion or sound is detected
- Email or FTP notification triggered by motion detection

- Wireless connectivity compliant with WPS button
- Instantly eliminates the dead zones and expand your home's wireless network
- Ethernet port for wired connectivity
- 4x digital zoom for close-up viewing
- Advanced H.264 video compression for smooth video streaming
- Support wireless 802.11b/g/n

2.3 Panel Appearance

2.3.1 Front Panel




Figure 2-1 Front Panel

- **Light Sensor:** The camera has a built-in internal photodetector. It is used to identify day or night.
- **Microphone:** The camera has a built-in internal microphone. This microphone is hidden in the pinhole located on the front panel.

➤ **System LED:**

Status	Indication
Flashing Red	The camera starts booting up.
Solid Red	The camera has boot up, but is not connected to any network.
Flashing Green	The camera is in firmware upgrade procedure.
Solid Green	The camera is connected to a network or is transferring data.

2.3.2 Rear Panel




Figure 2-2 Rear Panel

➤ **WPS LED:**

Status	Indication
Flashing Green	The camera starts booting up.
	The camera is connecting to a network by WPS function. This process will last in the first 2 minutes.
Off	The camera has boot up.
	The camera failed to be added to a network by WPS function.

Solid Green	The camera has been successfully added to a network by WPS function. This process will last in the first 2 minutes.
--------------------	---

- **Ethernet Port:** The ethernet port is used to connect the camera to a network via RJ45 cable.
- **Power Jack:** The power jack is where you connect the power adapter to the camera.
- **WPS/RESET Button:** This button is used for both WPS and RESET function. To use the WPS function, press it for 1 second. To use the RESET function, press and hold for more than 5 seconds.
 - **Used as the WPS button:**

If your wireless router supports WPS (Wi-Fi Protected Setup), you can connect the camera to your Wi-Fi network using WPS. Press the **WPS** or **QSS** button on your router. Within 2 minutes, press the **WPS/RESET** button on the camera for 1 second, then the WPS LED will start flashing quickly. When the LED becomes solid on, the camera is successfully connected to the router wirelessly..
 - **Used as the RESET button:**

With the camera powered on, press and hold the **WPS/RESET** button for more than 5 seconds until the System LED turns off. Then release the button and wait the camera to reset to its factory default settings.
- **Ventilation Holes:** These holes are used for heat dissipation.

Chapter 3 Set Up Your Camera

3.1 Set up the Camera with the tpCamera App

You can install your camera in minutes with the free tpCamera app. If your router has a WPS button, you can complete the setup wirelessly using WPS function. Please follow the steps below to set up your camera.

Step 1. Connect the camera to the network your smartphone is on.


Before you start the setup process, get your smartphone and make sure that it is connected to your home network.

Steps for connecting your camera to the router are:

- 1) Power on the camera using the provided power supply unit as shown.
- 2) Connect a smartphone to the router as shown.
- 3) Connect the camera to the router via wired or wireless connection, and then wait till the camera's system LED become solid green.

Wired: Connect the camera to the router's LAN port via an Ethernet cable.

Wireless: If your wireless router supports WPS, you can connect the camera to your Wi-Fi network using WPS. Press the **WPS** or **QSS** button on your router. Within 2 minutes, press the **WPS/RESET** button on the back of the camera for 1 second, then the WPS LED will start flashing quickly. When the WPS LED becomes solid on, the camera is successfully connected to the router wirelessly.



NC220	Day/Night Cloud Camera, 300Mbps Wi-Fi
NC230	HD Day/Night Wi-Fi Cloud Camera
NC250	HD Day/Night Cloud Camera, 300Mbps Wi-Fi

Step 2. Download and install the tpCamera app.

You can download the free **tpCamera** app from the App Store or Google Play. You can also scan the QR code below to download the tpCamera app.



Step 3. Add the camera to your TP-LINK cloud account.

Launch the tpCamera app, log in with your TP-LINK cloud account or create one if you do not have an account. Then follow the app instructions to add your new camera to your account.

When you reach the **My Cam** page, you have successfully added your camera and can start to use your camera.

3.2 Position Your Camera


Before positioning your camera, please keep these safety guidelines in mind:

- Keep your camera out of reach of children and pets.
- Use your camera only indoors, and keep it out of direct sunlight. Make sure its operating temperature is in the range of 0-40°C (32-104°F).
- Pick a location which is close enough to a wall outlet.
- Use only the power adapter that comes with this camera in the package.

You can place your camera to your desired location. Just unplug and replug it without having to go through the app’s setup again, and then you can use it in a wired or wireless way as you’ve set in the app’s setup process. If you use the camera wirelessly, please place the camera within the coverage of your wireless network. You can place the camera in various ways:


- Place it on a flat surface.
- Stick it with the included adhesive.
- Mount it to a wall or ceiling.

Detailed instructions on mounting your camera to a wall or ceiling are shown as follows. Before you start to mount the camera, prepare two screws which meet the following requirements.





1. Unscrew the camera head.

2. Remove the base cover.



3. Use two screws (not included) to secure the base.

4. Put the base cover and camera head back on.



After relocating your camera, face it towards the area you'd like to view, and then plug the power adapter into a power outlet.


Now that you've finished positioning your camera, use the tpCamera app to check that your camera can see what you want to keep an eye on. Adjust its position if needed.

Chapter 4 Configure Your Camera

You can use the tpCamera app and TP-LINK Cloud (<http://www.tplinkcloud.com>) to view and manage your camera remotely. To configure the camera's settings, such as the network settings, cloud settings, notification delivery, you should use the camera's built-in web management page in your local network.

4.1 Log in to Your Camera


1. Connect a computer to the router that your camera is connected to. You can use an Ethernet cable or connect it to the router's Wi-Fi network.
2. Find the IP address of the camera from the web management page of the router. Here we use the web management page of TP-LINK router for demonstration.




The screenshot shows the TP-LINK router's web management interface. The top navigation bar includes 'Quick Setup', 'Basic', and 'Advanced' tabs, along with 'Log out' and 'Reboot' buttons. The 'Basic' tab is selected, displaying a network map. The map shows the router connected to the Internet, with 15 wireless clients and 2 wired clients. Below the map, there are sections for 'Wireless Clients', 'Wired Clients', 'Printer', and 'USB Disk'. The 'Wired Clients' section is highlighted in green and contains a table with the following data:

ID	Name	IP Address	MAC Address
1	tplink-PC	192.168.0.102	D4:3D:7E:BF:61:5F
2	NC250 1.0	192.168.0.106	06:18:78:00:00:5B

3. On a computer that connects to the same router as the camera does, open a web browser, type in the camera's IP address in the address field, and press **Enter**. Here we use `http://192.168.0.106` for demonstration.




4. Enter the default username and password (**admin/admin**). Click **Login**.



The screenshot shows a login form with a username field containing 'admin', a password field with masked characters, a 'Remember account' checkbox, and a blue 'Login' button.

5. Create a new password for your camera to enhance security. Click **OK**.



The screenshot shows a password creation screen with the text 'Please create a password for your camera to enhance security:'. It includes a 'New Password' field with a strength indicator (Low, Middle, High) and a 'Confirm Password' field.

Note:


For the administrator, the default password is “admin”. For subsequent logins, use your password you have created.









If you log in to the camera as an administrator, you can perform all the settings provided by the camera.



If you log in to the camera as a common user, you can only view the Live View. After logging as administrator, you can add up to five user accounts in the Account menu (Go to “**System > Account**”).


4.2 Live View

The Live View screen shows you the live video feed from your camera. On this screen, you can also capture a picture.




Symbols	Meaning	Note
	Click to capture a still image shot by the camera.	The image file will be saved to your local computer. You can select a save path and rename the image file.
	Click to rotate the current image.	If the camera is installed upside down, Rotate Image should be checked.
  	Click to select the Auto/Day/Night mode.	 Auto: This mode will automatically switch between Day and Night modes based on the amount of available lighting.  Day: This sets the camera to always be in the Day mode.  Night: This sets the camera to always be in the Night mode.

- **Brightness:** Drag the **Brightness:**  slider to adjust the brightness level of camera. Large value will brighten the current displayed screen.
- **Contrast:** Drag the **Contrast:**  slider to adjust the contrast level of the camera. Large value will contrast the current displayed screen heavily.

- **Saturation:** Drag the Saturation:  slider to adjust the saturation level of the camera. Large value will saturate the current displayed screen to be more colorful.
- **Preset:** Click the **Preset** button to restore to factory image settings.

4.3 Basic

Click the **Basic** menu to display the submenus including **Status**, **Network**, **Wireless Connection**, **Cloud Setting**, and **LED**.



4.3.1 Basic > Status

The **Status** page displays the current configuration information of the camera. You can find out camera's settings such as wireless connection settings here. All the information is read-only.

Basic	
Camera Name:	NC250 1.0
Model:	NC250 1.0
Firmware Version:	1.0.5 Build 151106 Rel.24446
Current Viewers:	0
Cloud Server	
Connection Status:	Not registered
Username:	-
Wireless	
Connection Status:	Disconnected
Wireless Network Name:	-
Channel:	-
Rate/Signal Strength:	-
Security:	-
Network	
Connection Type:	Dynamic IP
MAC Address:	06-18-78-00-00-5B
LAN IP Address:	192.168.0.106
Subnet Mask:	255.255.255.0
Default Gateway:	192.168.0.1
Primary DNS Server:	192.168.0.1
Secondary DNS Server:	0.0.0.0
PPPoE	
Status:	Disconnected
WAN IP Address:	-
Video Profile	
Resolution:	1280*720
Frame Rate:	20FPS
Image Quality:	Normal
Light Frequency:	Auto

4.3.2 Basic > Network

On this page, you can configure your camera's IP address which is used to access and configure the camera.

- **Dynamic IP:** Select this option when a DHCP server is installed on the network to issue IP address assignment. With this setting, the IP address of the camera is assigned automatically.

The screenshot shows the 'IP Address' configuration section. At the top, the title 'IP Address' is followed by two radio button options: 'Dynamic IP' (which is selected) and 'Static IP'. A 'Save' button is located at the bottom right of the form.

- **Static IP:** Select this option when a static or fixed IP address is obtained for the camera. A static IP address will ease your access to the camera in the future. Add your camera's static IP information to your router to avoid IP conflicts.

The screenshot shows the 'IP Address' configuration section with 'Static IP' selected. Below the radio buttons, several fields are visible: 'MAC Address' (00-0C-43-76-20-21), 'IP Address' (192.168.1.100), 'Subnet Mask' (255.255.255.0), 'Default Gateway' (192.168.1.1), 'Primary DNS Server' (8.8.8.8), and 'Secondary DNS Server' (0.0.0.0). A 'Save' button is at the bottom right.

- **MAC Address:** Displays the Ethernet MAC address of the camera. The MAC address is read-only.
- **IP Address:** Enter a fixed IP address for the camera in dotted-decimal notation.
- **Subnet Mask:** Enter the subnet mask in dotted-decimal notation. The default value is "255.255.255.0."
- **Default Gateway:** Enter the default gateway in dotted-decimal notation.

- **Primary DNS Server:** Enter a DNS address in dotted-decimal notation.
- **Secondary DNS Server:** Enter a DNS address in dotted-decimal notation.

Click **Save** to save and enable the settings.

4.3.3 Basic > Wireless Connection

The camera's wireless function is enabled by default. This function helps to connect your camera to a wireless network wirelessly. If you don't want to use this function, just select the Disable option.

Wireless Connection

Enable
 Disable

Wireless Network List:

Wireless Network Name	Signal	Security	MAC Address
TP-LINK_1B0F28		None	54-E6-FC-1B-0F-28
TP-LINK_3G		None	00-0C-43-76-16-20
TP-LINK_EC6823		None	00-0A-EC-EC-68-23
TP-LINK_FFFFFFFF		None	FE-FF-FF-FF-FF-FF
TP-LINK_3G_2CBBB4		WPAWPA2-PSK	0C-82-68-2C-BB-B4
feng		None	A8-57-4E-F7-6E-20
3112AC		None	00-01-56-31-12-AC
TP-LINK_F9C62C		None	08-57-00-F9-C6-2C
0A5F2F		WPAWPA2-PSK	D4-CA-6D-0A-5F-2F
TP-LINK_M5_EC6612		WPAWPA2-PSK	5A-8F-CC-EC-66-12

Wireless Network Name: _____

- **Wireless Network Name:** Displays the wireless network's name. Make sure the camera and your PC connect to the same wireless network, or your PC can't access the camera.
- **Signal:** Displays the strength of the wireless signal.
- **Security:** Displays the wireless network's security mode.
- **MAC Address:** Displays the MAC address of the front device.

To connect your camera to a wireless network, follow the steps below:

1. Click **Scan** to scan the available wireless network and to refresh the Wireless Network List.
2. Select a wireless network from the wireless network list.
3. If the wireless network's security mode is **None**, simply click **Connect**. If the security mode requires a password, enter the wireless network's password and then click **Connect**. You can select **Show password** to display what you've entered.

Wireless Connection

Enable
 Disable


Wireless Network List:

Wireless Network Name	Signal	Security	MAC Address
TP-LINK_1B0F28		WPAWPA2-PSK	54-E6-FC-1B-0F-28
TP-LINK_3G		None	00-0C-43-76-16-20
TP-LINK_EC6823		None	00-0A-EC-EC-68-23
TP-LINK_FFFFFFFF		None	FE-FF-FF-FF-FF-FF
TP-LINK_3G_2CBBB4		WPAWPA2-PSK	0C-82-68-2C-BB-B4
feng		None	A8-57-4E-F7-6E-20
3112AC		None	00-01-56-31-12-AC
TP-LINK_F9C62C		None	08-57-00-F9-C6-2C
0A5F2F		WPAWPA2-PSK	D4-CA-6D-0A-5F-2F
TP-LINK_M5_EC6612		WPAWPA2-PSK	5A-8F-CC-EC-66-12


Wireless Network Name:

Password:
 Show password

4. A pop-up screen will prompt you for the network modification. Click **Change** to continue.



5. Click **OK** on the pop-up screen to finish wireless connection procedure.



6. To start using camera wirelessly, unplug its Ethernet cable.

4.3.4 Basic > Cloud Setting

A Cloud Camera can be viewed anytime and anywhere over the Internet with TP-LINK Cloud service. On this page, you can add the camera to your TP-LINK Cloud account.

 **Note:**

1. You can register a TP-LINK Cloud account in the tpCamera app only. If you do not get a tpCamera app, please refer to the **Step 2 Download and install the tpCamera app** in [3.1 Set up the Camera with the tpCamera APP](#).
2. To add a camera to your TP-LINK Cloud account, make sure that the camera is connected to the Internet.

Add Your Camera to TP-LINK Cloud Account

If you already have a TP-LINK Cloud account, to add your camera to your account, just enter the TP-LINK Cloud account and password, and then click **Register**.

Cloud Setting

Add your camera to Cloud account

Please enter your Cloud account and password:

Account:

Password:

Camera Name:

With Cloud service, you can view your cloud cameras anytime and anywhere over the Internet. Go to www.tplinkcloud.com.

- **Account:** Enter your TP-LINK Cloud account, either E-mail address or username is allowed.
- **Password:** Enter your TP-LINK Cloud account's password.
- **Camera Name:** The default value is the camera model. You can change it to an easy-to-remember one. Camera name can contain up to 31 characters. It cannot contain the following characters: \ / : = & ' " < > { }.

After your camera is registered successfully, you can go to <http://www.tplinkcloud.com> to view it.

4.3.5 Basic > LED


The camera's LED is on by default. If you want to turn it off, just select Off.

LED

LED: On Off

4.4 Advanced

Click the **Advanced** menu to display the submenus including **Status**, **Network**, **Wireless Connection**, **Wireless Extender**, **Cloud Setting**, **Video**, **Motion Detection**, **Sound Detection**, **Notification Delivery**, and **LED**.



4.4.1 Advanced > Status

Refer to [4.3.1 Basic > Status](#).

4.4.2 Advanced > Network

On this page, you can configure the network settings of the camera.

IP Address

Dynamic IP Static IP

Fallback IP:

HTTP

HTTP Port:

Bonjour

Bonjour: Enable Disable

Bonjour Name:

IP Address

On this section, you can configure your camera's IP address which is used to access and configure the camera.

- **Dynamic IP:** Select this option when a DHCP server is installed on the network to issue IP address assignment. With this setting, the IP address of the camera is assigned automatically.

IP Address

Dynamic IP Static IP

Fallback IP:

- **Fallback IP:** If the camera cannot get a Dynamic IP address from a DHCP server within limited tries, the camera will assign a default IP address, 192.168.0.10, by itself as the Fallback IP address.

- **Static IP:** Select this option when a static or fixed IP address is obtained for the camera. A static IP address will ease your access to the camera in the future. Add your camera's static IP information to your router to avoid IP conflicts.

IP Address

Dynamic IP Static IP

MAC Address: 00-0C-43-76-20-21

IP Address:

Subnet Mask:

Default Gateway:

Primary DNS Server:

Secondary DNS Server:

- **MAC Address:** Displays the Ethernet MAC address of the camera. The MAC address is read-only.
- **IP Address:** Enter a fixed IP address for the camera in dotted-decimal notation.
- **Subnet Mask:** Enter the subnet mask in dotted-decimal notation. The default value is "255.255.255.0."
- **Default Gateway:** Enter the default gateway in dotted-decimal notation.

- **Primary DNS Server:** Enter a DNS address in dotted-decimal notation.
- **Secondary DNS Server:** Enter a DNS address in dotted-decimal notation.

HTTP (Hypertext Transfer Protocol)

This feature allows you to access and manage your camera via its IP address. Web browser access normally uses the standard HTTP service port 80. The camera uses HTTP port 80 by default. For greater security, you can change the port to a custom one.

When HTTP port is set to 80, you can access the camera by typing its IP address (for example, http://192.168.1.100) on a web browser. When HTTP port is set to another value (for example, 2000), you need to type http://192.168.1.100:2000 instead.

The screenshot shows a configuration window titled 'HTTP'. Below the title, there is a label 'HTTP Port:' followed by a text input field containing the number '80'.

- **HTTP Port:** The default value is 80. If you want to use a port number other than **80**, enter a port number between 1 and 65535.

Bonjour

Bonjour, also known as zero-configuration networking, enables automatic discovery of computers, devices, and services on IP networks. Bonjour uses industry standard IP protocols to allow devices to automatically discover each other without the need to enter IP addresses or configure DNS servers.

The screenshot shows a configuration window titled 'Bonjour'. Below the title, there is a label 'Bonjour:' followed by two radio buttons: 'Enable' (which is selected) and 'Disable'. Below this, there is a label 'Bonjour Name:' followed by the text 'NC250-00005b'.

- **Bonjour:** To enable or disable the Bonjour service here.
- **Bonjour Name:** Displays the Bonjour name. By default, it is a combination of model and the last six characters of the camera's MAC address.

Click **Save** to save and enable the settings.

4.4.3 Advanced > Wireless Connection

The camera's wireless function is enabled by default. With this function enabled, you can connect your camera to a wireless network wirelessly. If you don't want to use this function, just select the **Disable** option.

On this page, you can either scan a wireless network to connect to or enter a wireless network's parameters manually. To scan a wireless network, refer to [4.3.3 Basic > Wireless Connection](#). To enter the parameters manually, see the following.

Wireless Connection

Enable Disable

Wireless Network List:

Wireless Network Name	Signal	Security	MAC Address
TP-LINK_1B0F28		WPAWPA2-PSK	54-E6-FC-1B-0F-28
TP-LINK_3G		None	00-0C-43-76-16-20
TP-LINK_EC6823		None	00-0A-EC-EC-68-23
TP-LINK_FFFFFFFF		None	FE-FF-FF-FF-FF-FF
TP-LINK_3G_2CBBB4		WPAWPA2-PSK	0C-82-68-2C-BB-B4
feng		None	A8-57-4E-F7-6E-20
3112AC		None	00-01-56-31-12-AC
TP-LINK_F9C62C		None	08-57-00-F9-C6-2C
0A5F2F		WPAWPA2-PSK	D4-CA-6D-0A-5F-2F
TP-LINK_M5_EC6612		WPAWPA2-PSK	5A-8F-CC-EC-66-12

Wireless Network Name:

1. Select **Enable** to enable your camera's wireless function.
2. Click **Manually**, and you will see the following screen.

Wireless Network Name:

Security:

3. In the Wireless Network Name field, enter the name of the wireless network to which your camera is ready to connect.

 **Note:**


The name must be exactly the same as that used in the wireless access point, or the connection will not be established. Leaving this field blank means the camera will attempt to access the nearest open network. If your PC wants to access the camera, make sure your PC and the camera are connecting to the same wireless network.

4. Select the wireless security mode used by your wireless network from the drop-down list. The security mode and its corresponding settings must be exactly the same as that used in the wireless network.
5. Click **Connect** and a screen will pop up. Click **Change** on the pop-up screen.
6. Click **OK** on the pop-up screen to finish wireless connection procedure.
7. To start using camera wirelessly, unplug its Ethernet cable.

4.4.4 Advanced > Wireless Extender

On this page, you can setup and configure the wireless network extending feature of your camera. Wireless extender function allows your camera to extend the range of your existing wireless network. You can use the same network name and settings as the existing wireless network, or you can create a new one.

The camera's wireless extender function is disabled by default. If you want to use this function, just select the **Enable** option.



----- **Wireless Extender** -----

Enable Disable

Host Wireless Network Name: TP-LINK_1B0F28

Extended Wireless Network Name: Same as Host

Max Clients: Unlimited

- **Host Wireless Network Name:** Displays the name of the wireless network which your camera is connected to. It is read-only.
- **Extended Wireless Network Name:** Name of the wireless network that your camera will extend.

- **Same as Host:** The extended network will use the same name and settings as your Host network. Your devices can use the same wireless information to connect to both the host and extended networks.
- **Create a New One:** Select this to manually set the name and security used for the extended network. You devices can use the wireless parameters you set to connect to the extended network.

----- **Wireless Extender** -----

Enable Disable

Host Wireless Network Name: TP-LINK_1B0F28

Extended Wireless Network Name: Same as Host
 test

Security: None

Max Clients: Unlimited

Save

- **Max Clients:** Set the maximum number of clients that are allowed to connect to the extended network.

Click **Save** to save and enable the settings.

4.4.5 Advanced > Cloud Setting

Refer to [4.3.4 Basic > Cloud Setting](#).

4.4.6 Advanced > Video

On this page, you can configure the video settings for your camera.

Video

Video Profile:

Coding Format	Resolution	Frame Rate	Mode	Image Quality
H.264	1280*720	15FPS <input type="button" value="v"/>	VBR	Normal <input type="button" value="v"/>

Backlight Compensation: Enable Disable

Light Frequency:


Time Stamp&On-Screen Display (OSD): Enable Disable

- **Coding Format:** Displays the video coding format of the camera.
- **Resolution:** Displays the video resolution of the camera. Higher resolution offers better quality, but will require more bandwidth to stream.
- **Frame Rate:** Select the frame rate to use for the video stream from the drop-down list. Higher settings offer smoother video streams, but will require more bandwidth.
- **Mode:** Displays the bit rate mode of the camera. This camera uses the VBR (variable bit rate) mode. In this mode, the bit rate varies to keep consistent video quality. It allows a higher bit rate (and therefore requires more bandwidth) to be allocated to dynamic scenes while less bit rate to be allocated to static scenes.
- **Image Quality:** Select the image quality from the drop-down list: Normal and Low. Normal settings offer better quality, but it may require more bandwidth to stream.
- **Backlight Compensation:** If enabled, this feature will compensate for bright backgrounds so foreground objects aren't silhouetted. It is disabled by default.

Enabled



Disabled



- **Light Frequency:** Select the frequency used by your lighting and power to help reduce image flicker. The default setting is auto, which is recommended.

- **Time Stamp&On-Screen Display (OSD):** If enabled, the current time of your camera, which can be set on the **System > Date/Time** page, will be displayed on the **Live View** screen. Meanwhile, you can set the OSD text to be displayed with the time stamp. The OSD text is camera name by default.

Enabled




Disabled



Click **Save** to save and enable the settings.

4.4.7 Advanced > Motion Detection

Motion detection allows you to specify areas of your camera's video to monitor for motion, which can be used to trigger snapshots. Refer to [4.4.9 Advanced > Notification Delivery](#) for more details.



- **Motion Detection:** To enable or disable the motion detection function. The area with blue mask indicates that it is the area with motion detection on. All areas are selected by default. You can drag your mouse to draw specific areas that you want to monitor.
- **Sensitivity:** Specify the level of difference between two sequential images that would indicate motion. Select one of the three levels of sensitivity from the drop-down list: High, Medium, and Low.

Click **Save** to save and enable the settings.

4.4.8 Advanced > Sound Detection

Sound detection allows your camera to detect a loud sound, which can be used to trigger snapshots. Refer to [4.4.9 Advanced > Notification Delivery](#) for more details.

Sound Detection

Sound Detection: Enable Disable

Sensitivity: ▼

Threshold: ▼

Tip: You can also drag the arrow to set the threshold for sound detection.

Save

- **Sound Detection:** To enable or disable the sound detection function.
- **Sensitivity:** Specify the level of difference between current sound and the threshold you set. Select one of the three levels of sensitivity from the drop-down list: High, Medium, and Low.
- **Threshold:** Select the threshold of sound level. Snapshots will be triggered when current sound exceeds this threshold. You can also drag the arrow in the diagram to set the threshold.

Click **Save** to save and enable the settings.

4.4.9 Advanced > Notification Delivery

Notification Delivery settings are available only after the motion detection or sound detection function is enabled. It is used to inform you immediately by sending the snapshots triggered by a detected motion or sound to the specified FTP server or E-mail address.

Notification Sending

Target: FTP
 E-mail

Save

FTP

Select **FTP**, you can configure your camera to send snapshots to a specified FTP sever on the following screen:

The screenshot shows a configuration window titled "Notification Sending". At the top, there is a "Target:" label with a checked checkbox for "FTP". Below this are several input fields: "FTP Server/Port:" followed by a text box and a separate box containing "21"; "Username:" followed by a text box; "Password:" followed by a text box; "Path:" followed by a text box containing "/"; and "Passive Mode:" with a checked checkbox. A "Test" button is located below the "Passive Mode" checkbox. At the bottom left, there is an unchecked checkbox for "E-mail". A "Save" button is located at the bottom right of the window.

- **FTP Server/ Port:** Enter the IP or the domain (IP/domain without prefix ftp://) and the port of the FTP server that you will be connecting to. The port is 21 by default.

Note:

The FTP server you set and the camera should be in the same LAN.

- **Username:** Enter the username that is used to log in to your FTP server.
- **Password:** Enter the password that is used to log in to your FTP server.
- **Path:** Enter the path to the destination on the FTP server.
- **Passive Mode:** Enabling passive mode may help you reach your FTP server if your camera is behind a router protected by a firewall.

To set up a FTP to receive notification, follow the steps below:

1. Enter an IP address or domain of your FTP server, e.g. 192.168.1.168
2. Remain the FTP port number as the default value: 21.
3. Enter your username to log in to the FTP server, e.g. test.
4. Enter your password to log in to the FTP server.
5. Enter the path to the destination on the FTP server, e.g. /test
6. Enable **Passive Mode**.
7. Click **Save** to save and enable the settings.

Click **Test**, and a test JPEG snapshot will be sent to the specified FTP server to check whether your settings are correct.

If the settings are tested correct, click **OK**.

If the settings are tested incorrect, check your network and FTP settings and try again later.

E-mail

Select **E-mail**, you can configure your camera to send snapshots to a specified E-mail address on the following screen.

Notification Delivery

Target: FTP
 E-mail

Recipient E-mail Address: [Add recipient](#)

Sender E-mail Address:

Password:

SMTP Server/Port: :

SSL Encryption: ▼

Sending Interval: ▼

Note: If you want to set Hotmail as sender E-mail Address, you need to set SMTP Server/Port as smtp-mail.outlook.com:25 (Or 587), and SSL Encryption as STARTTLS. If you want to set Gmail as sender E-mail Address, please refer to this link: <http://www.tp-link.com/en/faq-900.html>

- **Recipient E-mail Address:** Enter the receiver's E-mail address that the notification E-mail will be sent to. Click **Add recipient** to add receiver's E-mail addresses. You can specify up to four recipient E-mail addresses.
 - **Sender E-mail Address:** Enter the sender's E-mail address that is used to send the notification E-mail.
 - **Password:** Enter your password if the SMTP server uses authentication.
 - **SMTP Server/Port:** Enter the domain name or IP address and the port of your external E-mail server. The port is 25 by default.
 - **SSL Encryption:** Select TLS or STARTTLS as the SSL encryption; select **Close** to disable SSL encryption.
- Note:**
- If TLS is selected, SMTP server port should be 465; if STARTTLS is selected, SMTP server port should be 25 or 587.
- **Sending Interval:** Set the limit for how frequently E-mail notifications will be sent. Select one interval from the drop-down list.

For example, if you want to use Gmail with TLS for E-mail notifications, follow the steps below:

Notification Delivery

Target: FTP
 E-mail

Recipient E-mail Address: [Add recipient](#)

Sender E-mail Address:

Password:

SMTP Server/Port: :

SSL Encryption: ▼

Sending Interval: ▼

Note: If you want to set *Hotmail* as sender E-mail Address, you need to set SMTP Server/Port as *smtp-mail.outlook.com:25 (Or 587)*, and SSL Encryption as *STARTTLS*. If you want to set *Gmail* as sender E-mail Address, please refer to this link: <http://www.tp-link.com/en/faq-900.html>

1. Enter the receiver's E-mail address in Recipient E-mail Address, e.g. test@tp-link.com.
2. Enter your E-mail address in Sender E-mail Address, e.g. test@gmail.com.
3. Enter the password required to access the SMTP server.
4. Enter **smtp.gmail.com** in SMTP server.
5. Select **TLS** as the SSL encryption and the SMPT server port number will be changed to **465** automatically.
6. Set the Sending Interval, e.g. 1m.
7. Click **Save** to save and enable the settings.

Click **Test**, and a test JPEG snapshot will be sent to the recipient E-mail address to check whether your settings are correct.

If the settings are tested correct, click **OK**.


If the settings are tested incorrect, check your network and E-mail settings and try again later.

4.4.10 Advanced > LED

Refer to [4.3.5 Basic > LED](#).


4.5 System

Click the **System** menu to display the submenus including **Account**, **Date/Time**, **Management**, and **System Log**.



4.5.1 Account

On this page, you can change the administrator's password and manage the user account(s) that are allowed to access to your camera.



- **Username:** Displays the name of user account.
- **User Group:** Displays the group that the user account is in. Different user group has different limits of authority.
 - **admin:** This group has all authority of configuration. It can only have one account: admin.
 - **user:** This group can only view the Live View. It can have up to five accounts.

Add a New User Account

You can create a new user account to provide viewing access for your camera's video. User accounts will only be able to access the Live View section of the web configuration page, but cannot access any other parts or change any settings.

To add a new user account, follow the steps below:

1. Click **Add**, and you will see the following screen.

Account

User Name	User Group
admin	admin

Add
Change Password
Delete

Add a New User Account

Username:

Password:

Confirm Password:

2. Enter a username for your new account.
3. Enter a password for your new account. The password should contain 5 to 20 characters.
4. Enter the password again to confirm it.
5. Click **Save** to save and enable the settings.

Change Password

You can change the password of all the accounts here.

Note:

The default account and password are both **admin**. Everyone who knows the camera's IP address can access the device with all configuration authority. It is necessary to change the default password if the device is intended to be accessed only by administrator.

To change password, follow the steps below:

1. Select a user account in the list whose password you want to change
2. Click **Change Password**, and you will see the following screen.

Account

User Name	User Group
admin	admin
test	user

Change Password:

Current User: admin

Old Password:

New Password:

Confirm Password:

3. Enter the current password in the Old Password textbox.
4. Enter a new password.
5. Enter the new password again to confirm it.
6. Click **Save** to save and enable the settings.

Delete a User Account

You can delete a user account except admin here. Click a user entry in the list and click **Delete**.

4.5.2 Date/Time

On this page, you can configure the settings of the internal system clocks for your camera.

Date/Time

Time Configuration:

Current Time: 2015-11-06 10:50:28

Time Zone: (GMT) Greenwich Mean Time: Dublin, Edinburgh, Lisbon, London

Automatic Time Configuration:

Synchronize With NTP Server

Set Date And Time Manually:

Set Date and Time Manually

- **Current Time:** Displays the current date and time of the camera.
- **Time Zone:** Select the time zone for the region where the camera is installed.
- **Synchronize With NTP Server:** Select this option to specify the NTP server name to synchronize the date and time of the camera with those of the time server, known as the NTP (Network Time Protocol) server. If enabled, you will see the following screen:

Automatic Time Configuration:

Synchronize With NTP Server

NTP Service 0.pool.ntp.org << 0.pool.ntp.org

Set NTP Server from Dynamic IP

- **NTP Server:** You can either enter a domain name of the NTP server or select one which will be filled in automatically from the drop-down list.
- **Set NTP Server from Dynamic IP:** You can use the NTP server applied in the DHCP server on the network.
- **Set Date and Time Manually:** Select this option to set the date and time of the camera manually. If enabled, you will see the following screen:

Set Date And Time Manually:

Set Date and Time Manually

Year: Month: Day:

Hour: Minute: Second:

- **Copy Your Computer's Time Settings:** Click this button to copy your computer's current time settings.

Click **Save** to save and enable the settings.

4.5.3 Management

On this page, you can reboot the camera, backup and restore the camera's current settings, reset factory settings, and update the camera's software.

----- **Reboot** -----

Reboot your camera:

----- **Backup and Restore** -----

Back up current settings:

Restore settings from a backup file:

Restore factory default settings:

----- **Update** -----

Upgrade from a file on your hard disk:

- **Reboot:** Click **Reboot** and then click **Reboot** on the pop-up screen to confirm. Rebooting will not change the camera's setting. After rebooting, you need to log in to this page again.

- **Backup:** Click **Backup** and follow the instructions on the browser to save the setting data file to your specified location.
- **Restore:** Click **Browse** to locate the saved backup file and then click **Restore**. The camera will start rebooting and then the settings will be restored to the previous configuration.
- **Reset:** Click **Reset** and then click **Reset** on the pop-up screen to restore the camera to its factory defaults. Don't turn off the camera while resetting. After resetting, you need to find out the IP address of your camera (refer to [4.1 Log in to Your Camera](#)) and use the default username and password (admin/admin) to log in to this page.
- **Update:** Before update, download the latest firmware from the product page at <http://www.tp-link.com>, and then use decompression software to extract the file. Click **Browse** to locate the latest downloaded software file, and then click **Upgrade** to update the camera's software to the latest version. Wait for the upgrading process to complete, and the camera will reboot automatically.

 **Note:**

1. We recommend that you use a wired connection for your camera and PC when upgrading firmware.
2. The firmware upgrade procedure must not be interrupted or the camera may be damaged.
3. The firmware upgrade procedure is always risky and do not try to upgrade new firmware if it's not necessary.

4.5.4 System Log

On this page, you can review any changes and events happened to your camera. The system starts logging automatically after startup.

System Log

Time	Module	Level	Content
[2015-11-06/10:43:25]	MotionDetection	INFO	Motion Detection, Setting Succeed
[2015-11-06/10:41:15]	MotionDetection	INFO	Motion Detection, Get setting success.
[2015-11-06/10:40:21]	MotionDetection	INFO	Motion Detection, Setting Succeed
[2015-11-06/10:40:20]	MotionDetection	INFO	Motion Detection, Get setting success.
[2015-11-06/10:39:44]	MotionDetection	INFO	Motion Detection, Setting Succeed
[2015-11-06/10:39:44]	MotionDetection	INFO	Motion Detection, Get setting success.
[2015-11-06/10:28:47]	MotionDetection	INFO	Motion Detection, Get setting success.
[2015-11-06/10:28:45]	NetSwitch	INFO	new lan gw : 192.168.0.1.
[2015-11-06/10:28:45]	NetSwitch	INFO	new lan ip : 192.168.0.120.
[2015-11-06/10:28:34]	NetSwitch	INFO	new link status : Wired.

Level: Module:

Refresh Save Log Clear Log

- **Time:** Displays the time when the log event occurs. The log can get the correct time after you configure on the Date/Time page. (go to **Advanced > Date/Time**)
- **Module:** Displays the module to which the log information belongs. You can specify the module by selecting one from the Module drop-down list at the bottom.
- **Level:** Displays the severity level of the log information. You can specify the level by selecting one from the Level drop-down list at the bottom.
- **Content:** Displays the details of the log information.
- **Refresh:** Click **Refresh** to refresh the log information.
- **Save Log:** Click **Save Log** and follow the instructions on the browser to save the log to your specified location.
- **Clear Log:** Click **Clear Log** to clear all the log information.